

Certificate of Compliance

Certificate Number:

UL-CA-L182378-352618-71013102-2

Report Reference:

E182378-20131017

Issue Date:

2024-01-11

Issued to:

**R. STAHL Schaltgeraete GmbH
Am Bahnhof 30 Waldenburg, Baden-Wuerttemberg 74638
Germany**

This certificate confirms that representative samples of:

NWFN7 - Auxiliary Devices for Use in Zone Classified Hazardous Locations Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

CSA C22.2 NO. 60079-1, 3rd Ed., Issue Date: 2016-05-01, CSA C22.2 No. 60079-7, Edition 2, Issued 2016-10-01, CSA C22.2 NO. 14-18, 13th Ed., Issue Date: 2018-03-01, CSA C22.2 NO. 60079-0:19, 4th Ed., Issue Date: 2019-02-01

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L182378-352618-71013102-2
Report reference E182378-20131017
Date 2024-01-11

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
8006/4,, Type number may be followed by three digits, followed by 0, 1, 2 or 3, followed by 0, 6 or 8, may be followed by 1 or 2. For use in Ex db eb IIC T6...T4 Gb Hazardous Locations.	Control Switches



David Piecuch
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

