

TEST REPORT
IES LM-79-08
Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products.

Intertek Report No......: **ULR-TC622821000001228F**
Date of Report issue.....: 21-Oct-2021
Total number of pages.....: 12

Testing Laboratory.....: **Intertek India Private Limited**
Address.....: E-26, Block B1, Mohan Co-Operative Industrial Area,
 Mathura Road, New Delhi -110044, India

Customer / Applicant's name.....: **R. STAHL Private Ltd.**
Address.....: Plot No. 5, Malrosapuram Main Road | Sengundram Ind. Area |
 Singaperumal Koil Kancheepuram Dist | Tamilnadu | PIN 603 204 | India

Discipline.....: Photometry
Product Group.....: Light Sources (Electric Lamp)

Test specification:
Standard.....: IES LM-79-08
Non-standard test method.....: N/A

Test Report Form No......: LFT-APAC-IN-OP-10p Version: 17th Jun 2020

Test item description.....: **LED pendant light 65W (Narrow voltage version),5700K, With reflector**
Trade Mark.....: **STAHL**
Manufacturer.....: R. STAHL Private Ltd.
Model/Type reference.....: 6057,6457-65W (Narrow Voltage version)
Ratings.....: 230V AC, 50Hz, 65W, 0.276A

Tested by (Name + Signature + Function).....: VIJAY KUMAR
 (Engineer) 
Reviewed by (Name + Signature + Function).....: HARI OM 
 (Technical Leader - Lighting)

An independent organization testing for safety, performance, and certification.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Registered Office: Intertek India Private Limited,
 E-20, Block B1, Mohan Co-operative Industrial Area, Mathura Road, New Delhi-110 044, India
 Tel: +91-11-4159 5460, Facsimile: + 91-11- 4159 5475 © 2021 Intertek

General product information:

The LED Light is provided with Supply cord for supply connection.

LED Binning details: L2C5-57801211F1900

LED Details*:

Make: ---, **Model:** ---, **No. of LEDs:** ---

LED Controlgear/Driver Details*:

Make: ---, **Model:** ---, **No. of LED Drivers:** ---

COB provided with Lenses/ Glass.....: Yes /No.

Note:

*As declared by the Customer / Applicant.

Testing:

Date of receipt of test item.....: 29-Sep-2021
Condition of Sample Received.....: Physically Good
Sample Identification no(s).....: D26210929-005
Sample Serial no(s).....: Not provided
Date (s) of performance of tests.....: 06-Oct-2021

Laboratory conditions:

Ambient Temperature.....: 25 ± 4°C
Relative humidity.....: Less than 70 %

General remarks (If any):

The test results reported in this report relate only to the sample tested.
This report shall not be reproduced, except in full, without the written approval of report issuing testing laboratory.

Remarks:

The results tabulated in this report are representative of the actual test sample(s) submitted for this report only. The data is provided to the customer for further evaluation. Compliance to the referenced specification requirements is not determined in this report.

SUMMARY OF TEST RESULTS		
Sr. No.	Tests performed (name of test and test clause)	Verdict
1.	Electrical and Photometric measurements (Clause 8, 9, 10 and 11)	To be evaluated by customer
2.	Colorimetric measurements (Clause 12)	To be evaluated by customer

EQUIPMENTS USED				
Sr. No.	Equipment ID	Equipment name	Last calibration date	Next calibration date
1	ETL-LED-0094	High Speed Type-C Goniophotometer	Verified before use	Verified before use
2	ETL-LED-0095	Luminous Intensity Standard Lamp	05-Oct-2015	After 50Hrs. burning time
3	ETL-LED-0096	Luminous Intensity Standard Lamp	05-Oct-2015	After 50Hrs. burning time
4	ETL-LED-0097	Luminous Intensity Standard Lamp	05-Oct-2015	After 50Hrs. burning time
5	ETL-LED-0100	Digital Power Meter	12-Mar-2021	11-Mar-2022
6	ETL-LED-0105	Integrating Sphere	Verified before use	Verified before use
7	ETL-LED-0106	Spectral Flux Calibrated Standard Lamp	11-Nov-2015	After 50Hrs. burning time
8	ETL-LED-0111	Digital Power Meter	10-Jun-2021	09-Jun-2022
9	ETL-LED-0291	Humidity-cum Temperature Meter	19-Aug-2021	18-Aug-2022

Test No.01 Electrical and Photometric measurements - Distribution Method

TEST METHOD:

A LSI Type C High Speed Model 6440 Mirror Goniometer was used to measure the intensity (candelas) at each angle of distribution for each sample. Photometric distance was more than five times of the largest dimension of the test sample i.e. 8.63meter.

Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. The ambient temperature was maintained at $25\pm 1^{\circ}\text{C}$ during testing.

Sample was operated at input rated voltage in its designated orientation as specified by Manufacturer.

Electrical measurements including voltage, current, and power were measured using the power meter.


Each sample was allowed to stabilize for at least thirty minutes before measurements were made. The condition of the sample tested was new. Stabilization time before testing was **30** minutes.

TEST RESULTS

Input Voltage (Vac)	Input Frequency (Hz)	Current (A)	Power (W)	Power Factor
230.20	50.0	0.271	60.67	0.971

Total Luminous Flux (lm)	Luminous Efficacy (lm/W)
6462.0	106.5

INTENSITY(CANDLEPOWER) SUMMARY:



*** THIS IS AN ABSOLUTE TEST ***

LUMINANCE SUMMARY CD./SQ.M.

ANGLE	MEAN CD/SQ M		
45	509769		
55	734427		
65	214881		
75	124788	S/MH:	1.3
85	180510	SC:	1.3

TESTED IN ACCORDANCE WITH IES PROCEDURES.

INTENSITY (CANDLEPOWER) DATA:

ANGLE	INTENSITY (CANDLEPOWER)	LUMENS
0	2179	
5	2166	209
10	2148	
15	2129	600
20	2073	
25	2028	937
30	1987	
35	1826	1150
40	1710	
45	1568	1256
50	1704	
55	1832	1504
60	1180	
65	395	489
70	181	
75	140	149
80	104	
85	68	79
90	51	
95	44	48
100	37	
105	22	24
110	9	
115	6	7
120	5	
125	4	4
130	3	
135	3	2
140	3	
145	3	2
150	4	
155	4	2
160	5	
165	6	2
170	6	
175	7	1
180	7	

AVERAGE LUMINANCE DATA:

CD./SQ.M (FOOTLAMBERTS)		
ANGLE	LUMINANCE	
0	499081	(145664)
30	525361	(153334)
40	511277	(149223)
45	509769	(148783)
50	607267	(177239)
55	734427	(214353)
60	540544	(157765)
65	214881	(62716)
70	121530	(35470)
75	124788	(36421)
80	137115	(40019)
85	180510	(52684)



Total Quality. Assured.

COEFFICIENTS OF UTILIZATION:

ZONAL CAVITY METHOD

EFFECTIVE FLOOR CAVITY REFLECTANCE = .20

CC WALL	90				80				70				50				30				10				0	
	70	50	30	10	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0				
RCR	0	1.221	.221	.221	.22	1.191	.191	.191	.19	1.161	.161	.161	.16	1.101	.101	.101	.10	1.051	.051	.051	.05	1.011	.011	.011	.01	0.99
1	1.131	.081	.051	.01	1.101	.061	.030	.99	1.071	.041	.010	.97	0.990	.970	.94	0.950	.930	.91	0.920	.900	.88	0.86				
2	1.040	.970	.910	.85	1.020	.950	.890	.84	0.990	.930	.880	.83	0.890	.850	.81	0.860	.820	.79	0.830	.800	.77	0.75				
3	0.960	.860	.790	.73	0.940	.850	.770	.72	0.910	.830	.760	.71	0.800	.740	.70	0.770	.730	.68	0.750	.710	.67	0.65				
4	0.890	.770	.690	.63	0.870	.760	.680	.62	0.840	.750	.670	.62	0.720	.660	.61	0.690	.640	.60	0.670	.630	.59	0.57				
5	0.820	.690	.600	.54	0.800	.680	.600	.53	0.770	.670	.590	.53	0.640	.580	.52	0.620	.560	.52	0.600	.550	.51	0.49				
6	0.760	.610	.530	.46	0.730	.600	.520	.46	0.710	.590	.510	.46	0.570	.500	.45	0.560	.490	.45	0.540	.480	.44	0.42				
7	0.680	.540	.460	.40	0.660	.530	.450	.39	0.650	.520	.440	.39	0.510	.430	.38	0.490	.430	.38	0.480	.420	.37	0.36				
8	0.630	.490	.400	.34	0.610	.480	.400	.34	0.600	.470	.390	.34	0.460	.390	.34	0.450	.380	.33	0.430	.370	.33	0.31				
9	0.580	.440	.360	.30	0.570	.440	.350	.30	0.550	.430	.350	.30	0.410	.340	.29	0.400	.340	.29	0.390	.330	.29	0.27				
10	0.540	.400	.310	.26	0.530	.400	.310	.26	0.510	.390	.310	.26	0.380	.310	.26	0.370	.300	.26	0.360	.300	.25	0.24				

THE ABOVE COEFFICIENTS HAVE BEEN CALCULATED BASED ON LUMINAIRE LUMENS
 BECAUSE IN AN ABSOLUTE TEST THE BARE LAMP LUMENS ARE UNKNOWN.
 LIGHTING DESIGN CALCULATIONS MADE USING THESE COEFFICIENTS SHOULD
 THEREFORE USE THE LUMINAIRE LUMENS IN THE CALCULATION FORMULA

LABORATORY RESULTS MAY NOT BE REPRESENTATIVE OF FIELD PERFORMANCE.
 BALLAST AND FIELD FACTORS HAVE NOT BEEN APPLIED.

TEST DISTANCE EXCEEDS FIVE TIMES THE GREATEST
 LUMINOUS OPENING OF LUMINAIRE.



Total Quality. Assured.

Test No.02 Colorimetric Measurements - Integrating Sphere Method

TEST METHOD:

A Labsphere Three Meter Integrating Sphere was used to measure correlated color temperature, chromaticity coordinates and the color rendering index for each sample. 4π geometry was used.

Orientation (burning position) of product during testing was its normal burning position as specified by manufacturer.

Ambient temperature was measured at a position inside the sphere and was maintained at 25 ± 1 °C during testing.

Sample was allowed to stabilize for at least thirty minutes before measurements were made. The Stabilization time for the sample was **106** minutes. The condition of the sample tested was new.

Electrical measurements including voltage, current, and power were measure using the Power Meter.

The calibration of the sphere spectroradiometer system is traceable to the National Institute of Standards and Technology.


TEST RESULTS

Spectral Distribution


Dominant Wavelength nm	Radiant Flux	Purity	Peak Wavelength nm
552	19.204	4.291	452

CCT		CRI		x		y		Duv		u'		v'	
5485.0		83.0		0.3328		0.3479		0.0033		0.2045		0.4810	
R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14
80.8	88.7	93.2	81.7	81.6	83.6	87.1	67.1	5.02	72.5	80.4	62.4	83.0	96.5


Spectral Data over Visible Wavelengths



SAMPLE PHOTOGRAPHS:



Front View



Rear View



Side View

*******End of report*******