



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

**CERTIFICATE NO.:** 2020322317002653

**NAME AND ADDRESS OF THE APPLICANT**

R.STAHL Schaltgeräte GmbH  
Am Bahnhof 30,74638, Waldenburg, Germany

**NAME AND ADDRESS OF THE MANUFACTURER**

R.STAHL Schaltgeräte GmbH  
Am Bahnhof 30,74638, Waldenburg, Germany

**NAME AND ADDRESS OF THE FACTORY**

R. STAHL PRIVATE LIMITED  
Plot No. 5, Malrosapuram Main Road, Sengundram Ind. Area, Singaperumal Koil, Chengalpattu  
Dist, Chennai, Tamilnadu, India

**NAME, SERIES, MODEL AND SPECIFICATION**

Junction and Terminal Box  
8118 series

**THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS**

GB/T 3836.1-2021, GB/T 3836.3-2021, GB/T 3836.4-2021, GB/T 3836.9-2021, GB/T 3836.31-2021

This is to certify that the above-mentioned product(s) complies with the requirements of  
implementation rules for compulsory certification (CNCA-C23-01:2024).

Issue date: 2025-09-25 Valid until: 2030-09-24

Date of initial issue: 2020-09-30

Type of Certification: Type test + Initial inspection + Surveillance inspection

The certificate details and validity can be verified by scanning the QR code below or logging into the  
issuing authority's official website. It can also be inquired on the CNCA website ([www.cnca.gov.cn](http://www.cnca.gov.cn)).

(In case of dispute, the Chinese text shall prevail.)



**SITIILAS**  
Worldwide Access

APPROVAL:



**Shanghai Inspection and Testing Institute of Instruments and Automation Systems Co., Ltd.**



# 中国国家强制性产品认证证书

证书编号: 2020322317002653

认证委托人名称及地址

R.STAHL Schaltgeräte GmbH  
Am Bahnhof 30, 74638, Waldenburg, Germany

生产者名称及地址

R.STAHL Schaltgeräte GmbH  
Am Bahnhof 30, 74638, Waldenburg, Germany

生产企业名称及地址

R. STAHL PRIVATE LIMITED  
Plot No. 5, Malrosapuram Main Road, Sengundram Ind. Area, Singaperumal Koil,  
Chengalpattu Dist, Chennai, Tamilnadu, India

产品名称和系列、型号、规格

接线盒  
8118 系列

产品标准和技术要求

GB/T 3836.1-2021、GB/T 3836.3-2021、GB/T 3836.4-2021、GB/T 3836.9-2021、  
GB/T 3836.31-2021

上述产品符合《强制性产品认证实施规则 防爆电气》  
(CNCA-C23-01:2024)的要求, 特发此证。

发证日期:2025 年 09 月 25 日 有效期至:2030 年 09 月 24 日

首次发证日期:2020 年 09 月 30 日

认证模式:型式试验+初始工厂检查+获证后监督

证书信息和有效性可扫描下方二维码或登录发证机构网站查验,  
也可在认监委网站 ([www.cnca.gov.cn](http://www.cnca.gov.cn)) 查询。



批 准:

邵毅华

上海仪器仪表自控系统检验测试所有限公司





# 中国国家强制性产品认证证书

证书编号: 2020322317002653

证书附页: 第 1 页 共 2 页

产品名称:

接线盒

型号规格:

8118/b/c/d

b 代表设计代号, 可为 1 (Ex e) 或 2 (Ex i);

c 代表外壳尺寸, (长度 x 宽度 x 高度), 可为 1 (85x85x55mm),  
2 (115x115x64mm) 或 3 (145x145x71mm);

d 代表规格, 可为 0 (空外壳), 1 (接线盒), 2 (终端盒),  
3 (带熔丝的接线盒) 或 4 (带熔丝的终端盒)。

防爆标志:

Ex eb ia ib [ia Ga] mb II A/II B/II C T6...T4 Gb,

Ex tb III C T80°C...T130°C Db

电气参数:

|      |                                                  |
|------|--------------------------------------------------|
| 额定电压 | 最大值 1100V (无熔丝终端盒)                               |
|      | 最大值 550V (带熔丝终端盒)                                |
|      | 最大值 750V (接线盒)                                   |
| 额定电流 | 最大值 50A                                          |
| 横截面积 | 1 或 2x1.5 至 10mm <sup>2</sup> 硬线或软线, 带或不带<br>端芯套 |

相关报告编号:

2020S17402-003696

2023S17402-011970

使用条件:

1. 特殊 (限制) 使用条件

1) 该产品的使用环境温度范围为-60°C~+75°C。

本页为证书附页, 应与证书主页同时使用。



**SITI**AS  
Worldwide Access

批 准:

邵长华



上海仪器仪表自控系统检验测试所有限公司



# 中国国家强制性产品认证证书

证书编号：2020322317002653

证书附页：第 2 页 共 2 页

产品使用环境温度可能会因为选用防爆部件功率及使用环境温度或使用工作温度而减少，需同时参考防爆部件证书及说明书相关信息。

- 2) 应考虑防爆部件的特殊（限制）使用条件对整机的影响。
2. 该产品的外壳防护等级为 IP66。
3. 所有螺纹盖的紧固力矩为  $1.4\text{N}\cdot\text{m}$ 。
4. 该产品作为 Ex-i 产品使用时，产品必须与经防爆认可的关联装置配套共同组成本安防爆系统方可适用于现场存在爆炸性气体混合物的危险场所，其系统接线必须同时遵守接线盒及选用本安防爆部件和所配关联装置的使用说明书要求，接线端子不得接错。

该产品与关联装置的连接电缆应为带绝缘护套的屏蔽电缆，其屏蔽层应接地。

本页为证书附页，应与证书主页同时使用。



**SITI**AS  
Worldwide Access

批 准：

上海仪器仪表自控系统检验测试所有限公司