WaterTank-Easypump-Automatic-TXWP7 Art. No. 339164



- Innovative explosion-proof Easypump washing system
- Eliminates the need to manually pressurise the water tank; the only requirement is manual refilling
- Tank capacity 15 l, low-level sensor, 15 m delivery head
- Approvals: ATEX, IECEx, UKCA, INMETRO, ECAS

MY R. STAHL

The Easypump washing system revolutionises the cleaning of CCTV cameras in hazardous environments by eliminating the need for manual tank pressurisation. A special pump is used to spray water from the integrated reservoir. This new concept does away with the need to manually pressurise the tank – the only requirement being that it is refilled – whilst guaranteeing a constant flow rate and pressure at all times. The Easypump washing system is specifically designed for use in hazardous areas. The 15-litre reservoir tank is integrated, and a low-level sensor can alert the operator if the fluid level is too low. The housing is made of AISI 316L stainless steel and features an integrated bracket for wall mounting.

Technical Data

General	
Version	Watertank Solution
Description	Water tank with float switch, with automatic pump stop and remote alarm signal
Explosion Protection	
Scope	EU (CE / ATEX) Global (IECEx) United Kingdom (UKCA) Brazil (INMETRO) United Arab Emirates (UAE)
EMC Directive	EN 55032; EN/IEC 61000-3-2; EN/IEC 61000-3-3; EN/IEC 61000-6-2; CISPR-32
RoHS Directive	2011/65/EU + 2015/863/EU (RoHS 3)
WEEE Directive	2012/19/EU
Low-voltage Directive	EN/IEC 62368-1
FCC certification	FCC part 15B
Electrical Data	
Power supply	100 – 240 VAC
Power consumption	10 W
Ambient Conditions	
Temperature range	-60 °C ... +60 °C, +75 °C peak
Mechanical Data	
Capacity	15 l
Delivery head	up to 15 m
Washing cycles	5 s cycle
Fluid outlet	15 m hose, 4 mm bore tube
Hose material	Black antistatic polyurethane, UV resistant

R. STAHL HMI Systems GmbH | Adolf-Grimme-Allee 8 | 50829 KÖLN
Tel. +49 221 768 06 1200 | +49 221 768 06 4200 | Email: sales.dehm@r-stahl.com | r-stahl.com

WaterTank-Easypump-Automatic-TXWP7 Art. No. 339164

Mechanical Data

Float switch	with automatic pump stop and remote alarm signal
Type of installation	Wall mounting
Degree of protection (IP)	IP66 / IP67
Enclosure	AISI 316L stainless steel, electropolished
Dimensions (WxHxD)	293 mm x 413 mm x 332 mm
Weight	12 kg
Weight	26.46 lb

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.

R. STAHL HMI Systems GmbH | Adolf-Grimme-Allee 8 | 50829 KÖLN
Tel. +49 221 768 06 1200 | +49 221 768 06 4200 | Email: sales.dehm@r-stahl.com | r-stahl.com