

IS530.RG Smartphone Set ROW 订货号 306013



- Universal, 13-pin ISM (multifunctional) interface for connecting additional devices for a wide range of applications
- Android Enterprise Recommended
- zero touch capable
- MDM compatible

<STEPREF A="AT_TitleWeb-shop" O="PV 2244175"

With its ISM interface, the powerful, industrial smartphone has many applications. Other additional modules such as an RSM, PTT headsets, the professional IS-TH1xx.1 barcode scanner and the IS-TC1A.1 thermal imaging camera make the IS530.1 smartphone a high-performance, multifunctional device. The smartphones are Android Enterprise Recommended, zero touch capable and MDM compatible.

技术数据

防爆

使用范围 (区)	Non-Ex
应用范围	Industrial, rugged
电气数据	
处理器型号	Qualcomm SDM660 Octa-core
内存	4 GB
数据存储器	64 GB 内存 + 高达 128 GB 的 SD 卡
操作系统	Android 10 (upgr. 13)
移动标准	2G , 3G , 4G
介质接口	WLAN 802.11 a/b/g/n/ac/e/k/r/h
附加接口 1	蓝牙 5
可选数据接口 2	13MP-AF-摄像头 (后置)
附件 3/选项框	5MP 前置摄像头
SD 卡型号/容量	microSD/最大 128 GB
SIM卡号	双 SIM 卡
SIM 卡尺寸	micro
显示屏	
显示屏尺寸, 英寸	4.50
显示屏尺寸 cm	11.43
显示屏分辨率	FWVGA
触摸屏	电容式
触摸屏材料	大猩猩玻璃, 康宁第三代
背光照明灯	LED 技术
环境条件	
环境温度	-20 – 60
环境温度	-20 °C ... +60 °C

IS530.RG Smartphone Set ROW 订货号 306013

机械数据

防护等级 (IP)	IP68
MIL 标准	810G (h/l 温度, 冲击, 振动)
宽度	80 mm
高度	155 mm
深度	25 mm
重量	325 g
重量	0.72 lb

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。