

## IS-TH1MR.2 Trigger Handle Set 订货号 317631



- Reliable data capture and processing of 1D or 2D barcodes
- direct data transfer via ISM interface
- power supply via connected device, thus no battery required
- direct interface connection with device, no Bluetooth® required

<STEPREF A="AT\_TitleWeb-shop" O="PV 2700893"



The mobile multifunctional set consisting of a Trigger Handle (hand-held barcode scanner) and the IS530.x industrial smartphone is a flexible duo for reliable data capture in hazardous areas. The HID-active, ready-to-use high-performance scanner captures any 1D or 2D barcodes at close range of up to 6 metres or distances up to 18 metres via the reliable Zebra OEM imager scan engines. The data is further processed directly via the IS530.x smartphone connected via the ISM interface.

### 技术数据

#### 防爆

防爆版本	有
应用范围 ( 区域 )	2, 22
使用范围 (Division)	Class I, Division 2 Class II, Division 2 Class III, Division 2
适用范围	欧盟 (CE / ATEX) 全球 (IECEX) 美国 (NEC) 加拿大 (CEC)
IECEX 认证	EPS 21.0028X
ATEX 认证	EPS 21 ATEX 1 082 X
NEC 认证	70220252
CEC 认证	70220252
IECEX 气体防爆	Ex ic op is IIC T4 Gc
IECEX 粉尘防爆	Ex ic op is IIIC T135°C Dc
ATEX 气体防爆	Ⓢ II 3G Ex ic op is IIC T4 Gc
ATEX 粉尘防爆	Ⓢ II 3D Ex ic op is IIIC T135°C Dc
NEC 气体防爆	Class I, Div 2, Groups A, B, C, D, T4
NEC 粉尘防爆	Class II, Div 2, Groups F, G , T135°C Class III, Div 2
CEC 气体防爆	Class I, Div 2, Groups A, B, C, D, T4
CEC 粉尘防爆	Class II, Div 2, Groups F, G , T135°C Class III, Div 2

#### 环境条件

环境温度 -20 – 60

#### 机械数据

箱体防护等级 (IP) 正面 IP68

## IS-TH1MR.2 Trigger Handle Set 订货号 317631

---

### 机械数据

箱体防护等级 (IP) 背面	IP68
壳体材料	塑料
宽度	90 mm
高度	202 mm
深度	125 mm
重量	1 kg
重量	2.2 lb

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。