



- Certified for hazardous areas: Zone 1, 2, 21, 22, Class I, Div. I
- Indoor & outdoor use: offshore, onshore, ports, ships, chemical, pharmaceutical, hydrogen environments
- IP day/night camera with 4K Ultra HD, 22x optical zoom, image stabilization
- Low-maintenance design, low power consumption, IP66–69, NEMA 4X, NDAA-compliant, with integrated wiper
- Operating temperature range: –60 °C to +65 °C (peak +75 °C)

A9

MY R. STAHL EC932A



The EC-932 cameras offer state-of-the-art technology with 40x zoom for demanding surveillance tasks in the oil, gas, chemical and pharmaceutical industries. They are modular in design, field-serviceable and available with either standard or AVIGILON camera modules. The cameras are available for 120 V, 240 V AC or PoE+ and can be used around the clock in hazardous areas (Zones 1, 2, 21, 22, Class I Div. I) at temperatures ranging from –60 °C to +60 °C.

	IECEx / ATEX					
Zone	0	1	2	20	21	22
Installation in		•	•		•	•

Selection Table						
Day/night camera	Yes					
Compression	H.264, H.265, MJPEG					
Product Type	Rated operational voltage AC	Interfaces	Resolution	Zoom	Art. No.	Weight
EC-932-TXF3TV2W-SM-M	230 V	1x230 VAC, 1xRJ45	3 MP, 2065x1553 pixels	40x optical, 10x digital	338431	10.5 kg
EC-932-TXF5TV2W-IP-M	–	PoE+ (IEEE 802.3at Class 4)	3 MP, 2065x1553 pixels	40x optical, 10x digital	338360	10.5 kg
EC-932-TXF5TV4W-IP-M	–	PoE+ (IEEE 802.3at Class 4)	4 K, 3864x2180 pixels	22x optical, 10x digital	338432	10.5 kg
EC-932-TXFUS2TA01W-IP-M	120 V	1x110 VAC, 1xRJ45	2 MP, 1920x1080 pixels	18x optical	334041	10.5 kg



