



- Available in brass and stainless steel AISI 316 (EN 1.4401)

E6

MY R. STAHL T794-650A



Stopping plugs are required to close unused entries in enclosures. R. STAHL TRANBERG have a wide variety of stopping plugs, in various designs, and available in brass or stainless steel (316). This model is certified to both ATEX and IECEx. Development and manufacturing of this product is done at our factory in Stavanger, Norway.

Application:

- Outdoor or indoor.
- Suitable for use in hazardous area, zone 1, zone 2 and safe area.

Special conditions for use:

Blanking elements shall not be used with adaptors.

	IECEx / ATEX					
Zone	0	1	2	20	21	22
Installation in		•	•			

Selection Table							
Material		Brass					
Thread size	Outer diameter	Thread length	Width across flats	Width across corners	Old Art. No.	Art. No.	Weight
M16	27 mm	9 mm	24 mm	27 mm	6501600	259495	140 g
M16	27 mm	9 mm	24 mm	27 mm	6501602	259497	170 g
M20	30 mm	9 mm	27 mm	30 mm	6502000	259499	60 g
M20	30 mm	9 mm	27 mm	30 mm	6502002	259501	80 g
M25	36 mm	9 mm	32 mm	36 mm	6502500	259503	100 g
M25	36 mm	9 mm	32 mm	36 mm	6502502	259505	100 g
M32	47.5 mm	9 mm	42 mm	47.5 mm	6503200	259506	130 g
M32	47.5 mm	9 mm	42 mm	47.5 mm	6503202	259508	140 g
Material		Stainless steel					
Thread size	Outer diameter	Thread length	Width across flats	Width across corners	Old Art. No.	Art. No.	Weight
M16	27 mm	9 mm	24 mm	27 mm	6501605	259494	140 g
M16	27 mm	9 mm	24 mm	27 mm	6501607	259496	170 g
M20	30 mm	9 mm	27 mm	30 mm	6502005	259498	60 g
M20	30 mm	9 mm	27 mm	30 mm	6502007	259500	80 g
M25	36 mm	9 mm	32 mm	36 mm	6502505	259502	80 g

Selection Table

Material		Stainless steel						
Thread size	Outer diameter	Thread length	Width across flats	Width across corners	Old Art. No.	Art. No.	Weight	
M25	36 mm	9 mm	32 mm	36 mm	6502507	259504	100 g	
M32	47.5 mm	9 mm	42 mm	47.5 mm	6503205	259548	130 g	
M32	47.5 mm	9 mm	42 mm	47.5 mm	6503207	259507	140 g	

Technical Data

Explosion Protection	
IECEX gas certificate	IECEX NEM 13.0025X
IECEX gas explosion protection	Ex eb IIC Gb
ATEX gas certificate	NEMKO 13 ATEX 1553X
ATEX gas explosion protection	Ⓔ II 2 G Ex eb IIC Gb
Declaration of conformity	ATEX (EUK)
Ambient Conditions	
Ambient temperature	-60 °C ... +135 °C
Mechanical Data	
Degree of protection (IP)	IP66 / IP67
Drive	External hexagon
Sealing ring material	Silicone Shore A70 red
Silicone-free	No