

573 Ex Art. No. 278739



- Very good conductivity
- Easy maintenance inside the reel (no additional encapsulation)
- Resistant to oils and greases
- High mechanical strength
- Compact and robust
- Long service life

MY R. STAHL 8580A



The Series 8580 SolConeX cable reel is maintenance-free and resistant to chemical influences, UV light and weather.

The stable tubular steel frame and halogen-free solid rubber reel body guarantee high mechanical resilience.

The cable reel features a 30-m-long PROFLEX electrical line with a plug and is offered in two versions (3- or 5-pole).

Technical Data

Explosion Protection

Application range (zones)	1, 2
ATEX gas certificate	SEV 18 ATEX 0130
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC T6

Ambient Conditions

Ambient temperature	-20 °C ... +40 °C
---------------------	-------------------

Mechanical Data

Cable reel enclosure material	Butyl rubber
Degree of protection (IP)	IP66
Class	II
GI factor	1
Number of sockets	1
Conductor cross-section	3 x 2.5 mm ²
Conductor type	PROFLEX H07RN-F
Conductor length	30 m
Width	370 mm
Height	532 mm
Depth	408 mm
Weight	22 kg
Weight	48.5 lb

Components

Plug enclosure material	Polyamide, glass fibre reinforced
Number of poles on plug	3
Rated operating current plug	16 A
Rated operational voltage plug	200 to 250 V AC
Plug frequency	50/60 Hz

573 Ex Art. No. 278739

Components

Plug coding	6
Plug colour code	Blue
Socket enclosure material	Polyamide, glass fibre reinforced
Rated operating voltage socket 1	200 to 250 V AC
Socket 1 frequency	50/60 Hz
Rated operating current socket 1	16 A
Number of poles on socket 1	3
Socket 1 colour code	Blue
Socket 1 coding	6

Accessories

Plug

Art. No.




8570/12-306-S-XX-X-XX-XXX 3-pole plug, 200 to 250 V AC, 50 / 60 Hz, 16 A

272898

Protective cap for Series 8570 plug

Art. No.



3-pole

150496

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.