

8290/3-M63 Art. No. 285778



- Plastic stopping plugs for sealing open drilled holes
- For thread sizes from M16 to M63
- For Ex e enclosures

MY R. STAHL 8290A



R. STAHL's Series 8290 plastic stopping plugs can be used to seal unused drilled holes in Ex e enclosures ("increased safety" type of protection). To ensure that they remain robust during use, they are designed to be impact-resistant according to IEC/EN 60079-0 and IEC/EN 60079-7 and are protected against coming loose.

Technical Data


Explosion Protection	
Application range (zones)	1, 2, 21, 22
IECEX gas certificate	IECEX PTB 05.0013
IECEX gas explosion protection	Ex eb IIC Gb
IECEX dust certificate	IECEX PTB 05.0013
IECEX dust explosion protection	Ex tb IIIC Db
ATEX gas certificate	PTB 99 ATEX 3133
ATEX gas explosion protection	Ex II 2 G Ex eb IIC Gb
ATEX dust certificate	PTB 99 ATEX 3133
ATEX dust explosion protection	Ex II 2 D Ex tb IIIC Db
Certificates	ATEX (PTB), Brazil (ULB), China (CQST), IECEX (PTB), Korea (KGS)
Declaration of Conformity	ATEX (EUK), China (CCC)
Ambient Conditions	
Ambient temperature	-60 °C ... +80 °C
Mechanical Data	
Degree of protection (IP)	IP66
Degree of protection note	acc. to IEC/EN 60529
Sealing ring material	EPDM
Material	Polyamide, Glass fibre reinforced
Silicone-free	Yes
Self-extinguishing	Yes
Flame-retardant	Yes
Drive	Hexagon socket
Width across corners	75 mm
Width across flats	68 mm
Hexagon socket width across flats	10 mm
Thread size	M63
Thread length	14 mm

8290/3-M63 Art. No. 285778

Mechanical Data

Thread pitch	1,5 mm
Packaging unit	30
Weight	3.7 lb

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



M = Thread size

d = Width across corners

h1 = Thread length

h2 = Dimension h2

SW1 = Hexagon socket width across flats

SW2 = Width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.