

# Operating and Monitoring Systems

## Panel PC SERIES 400

### Device platform MANTA

### OS MT-477-SX



- Panel PC Operator Station, 24" display, Full HD 1920 x 1080
- Zone 2, 22, stainless steel enclosure IP66, optional acc. to GMP
- Optional resistive glass or foil touch screen
- Data transmission as 1000Base-SX via multi-mode fibre optic up to 550 m and as 10/100Base-TX via CAT7 up to 100 m

#### MY R. STAHL MANTAPCT-COSA



The OS MT-477-SX operator stations with MANTA device platform are explosion -protected Panel PCs for Zones 2, 22 and Division 2. Their brilliant 24" widescreen displays with a resolution of 1920 x 1080 pixels (format 16:9) are available with or without touch screen. The stainless steel enclosures (SS304 or SS316L) are available with a front opening in cleanroom-compliant design and with different mounting options. Configuration options include country-specific keyboards, pointer instruments, RFID readers and barcode readers, different memory sizes and SSDs. Data is transmitted via Ethernet as 1000Base-SX via multi-mode fibre optic up to 550 m and as 10/100Base-TX via CAT7 up to 100 m.

## Technical Data

### General

Series	MANTA Panel PCs / Thin Clients Operator Stations
Product description	24" Panel PC
HMI type	Operator Station
Technology	Panel PC

### Explosion Protection

Application range (zones)	2 22
Scope	EU (CE / ATEX) International (IECEX) China (CCC / CNEx) Australia (RCM)
IECEX certification	IECEX BVS 14.0034X
ATEX certification	BVS 12 ATEX E 033 X
CCC certification	2020312309000270
CNEx certification	CNEx14.2205X
Notice certification	The certificates and explosion protection markings apply to a standard device combination with display, keyboard and enclosure. These may vary with further installations and extensions.
IECEX gas explosion protection	Ex nA nR [ja op is Ga] IIC T4 Gc
IECEX dust explosion protection	Ex tc IIIC [ja op is Da] IP66 T110°C Dc
ATEX gas explosion protection	II 3(1) G Ex nA nR [ja op is Ga] IIC T4 Gc
ATEX dust explosion protection	II 3(1) D Ex tc IIIC [ja op is Da] IP66 T110°C Dc
CNEx gas explosion protection	Ex nA nR [ja op is Ga] IIC T4 Gc
CNEx dust explosion protection	Ex tc IIIC [ja op is Da] IP66 T110°C Dc

# Operating and Monitoring Systems

## Panel PC SERIES 400

### Device platform MANTA

### OS MT-477-SX



#### Electrical Data

Power supply	230 VAC
Rated operational voltage AC	230 V
Voltage range AC	100 – 240 V
Frequency range	50 – 60 Hz
Power consumption AC 1	1 A
Protection fuse AC	5 AT
Rated operational power	typically 50 W / max. 150 W (typically 170 BTU / max. 510 BTU)
Processor type	AMD GX-222GC
Processor details	2.2 GHz, Dual Core, 10W TDP
RAM	4 GB
Data memory	64 GB MLC 128 GB MLC
Graphics controller	integrated AMD Radeon R5E graphics
Memory technology	SSD solid state flash drive
Operating system	Windows 10 IoT Enterprise (64 bit) (included in standard delivery) Windows 10 IoT Enterprise (32 bit) (optional on USB stick)
Language support	via Windows operating system
Ethernet / Data	1x 1000Base-SX (Ex op is) 1x 10/100/1000Base-TX (Ex e)
Data cable	SX: 50/125 µm or 62,5/125 µm FO cable TX: CAT7 installation cable AWG23
Data cable length	SX: Max. 550 m for 50 µm or max. 275 m for 62,5 µm FO cable TX: Max. 100 m
Data cable notice	Minimum requirement CAT5e, recommended CAT7
Interface medium	SX: multi-mode optical cable TX: CAT7 data transmission
Interface USB	2 x USB (Ex ia) 1 x USB (Ex nA) 2 x USB (Ex ia) (keyboard, pointing device)
Interface serial	1 x RS-232 (Ex nA)
Interface reader	via USB or RS-232
Interface reader note	RFID reader, support of the following standards: MIFARE Classic, DESFire, DESFire EV1, LEGIC prime and advant, NFC, INSIDE Secure, Sony FeliCa, ISO 14443A & 15693 1D/2D Barcode scanner: support of all common 1D/2D codes, wired or Bluetooth
Interface audio	1 x Audio line out (Ex nA)
WLAN	optional via USB
Connection compartment	Power supply direct in integrated terminal box
Connections	via spring clamp terminals, green
Voltage output	12 VDC, max. 500 mA
Wiring	flexible cable up to 2.5 mm <sup>2</sup> (AWG14) fixed cable up to 4 mm <sup>2</sup> (AWG12)
Plug version FO	LC duplex socket
Max. input voltage U <sub>m</sub>	250 VAC
Real-time clock	Yes
Real-time clock data buffer	Lithium battery and capacitor buffered, maintenance-free
Battery buffered	> 5 years
Capacitor buffered	at least 4 days

# Operating and Monitoring Systems

Panel PC SERIES 400

Device platform MANTA

OS MT-477-SX



## Display

Display version	TFT Color display
Display version 2	16.7 million colours
Display size inch	24
Display size centimetres	61
Display resolution	1920 x 1080, 1680 x 1080, 1280 x 1024
Total pixels	1920 x 1080
Display dimensions	16:9
Display brightness	300 cd/m <sup>2</sup>
Display contrast	1000:1
Display viewing angle horizontal	178°
Display viewing angle vertical	170°
Touchscreen	optional, resistive glass or foil touchscreen
Touchscreen technology	5-wire glass or foil touch
Touchscreen activation	Foil touch: low activation pressure (0.1 to max. 1 N) Glass touch: medium activation pressure (1.8 to max. 2.5 N)
Touchscreen input method	Finger, gloved finger or stylus
Touchscreen durability	Foil touch: polyester foil is easily scratched, with high pressure the spacer dots could be damaged Glass touch: Satisfactory, but glass is not hardened, with high pressure the spacer dots could be damaged
Touch screen scratch hardness MoHS	Foil touch: - Glass touch: >5
Touchscreen scratch hardness pencil test ISO15184	Foil touch: 3H Glass touch: 9H
Touchscreen transmissivity / optic	Foil touch: slightly milky effect due to foil Glass touch: very good
Touchscreen surface contaminants	unaffected
Touchscreen abrasive resistance	36 million activations with a silicone rubber finger R8, 250 g for 2 activations per second
Backlight	LED Technology
Backlight service life	50000 h at +20 °C
Front plate (display)	Aluminium and no touchscreen: glass foil touchscreen: polyester glass touchscreen: thin glass
Function keys	optional via keyboard with integrated trackball, joystick or touchpad
Softkeys	optional via keyboard with integrated trackball, joystick or touchpad
Cursor keys	optional via keyboard with integrated trackball, joystick or touchpad
Alphanumeric keys	optional via keyboard with integrated trackball, joystick or touchpad
System keys	optional via keyboard with integrated trackball, joystick or touchpad
<b>Ambient Conditions</b>	
Ambient temperature operation	-20 °C ... +55 °C
Storage temperature	-30 °C ... +70 °C
Cold start temperature	-10 °C
Temperature note 2	Operating temperature +55 °C for a maximum of 5 h, for constant operation (24/7) +50 °C.

# Operating and Monitoring Systems

Panel PC SERIES 400

Device platform MANTA

OS MT-477-SX



## Ambient Conditions

Temperature note 3	Cold start temperature: If the HMI device is switched on at a temperature below -10 °C the display will need a certain amount of time to warm up until everything is clearly visible. Depending on how low the temperature is, this process may last up to 3 hours.
Temperature note general	The temperature details apply to a standard device combination with display, keyboard and enclosure. They may change accordingly with any additional built-in or added components.
Heat dissipation	about 40% via the front plate and 60% via the enclosure
Relative humidity	10 to 90% at +40°C [+104 °F], non-condensing
Damp heat cyclic	+55 °C (±2 °C) ≥95 % (only devices with glass touch (TG))
Dry heat	+65 °C
Vibration sinus	5 to 13.2 Hz: ±1 mm 13.2 to 100 Hz: ±0.7 g Change cycle 1 oct/min Axis X, Y, Z
Vibration sinus 1	71.7 to 79.2 Hz: ±0.7 g 120 min. Change cycle 1 oct/min Axis X
Vibration sinus 2	30 Hz: ±0.7 g 90 min. Change cycle 1 oct/min Axis Y, Z

## Mechanical Data

Dimensions (WxHxD)	740 mm x 872 mm x 400 mm
Material front	Aluminium / stainless steel
Material back	Stainless steel
Ingress protection	IP66
Weight	58.5 kg
Breather	optional
Keyboard note	Only for KBDi: For keyboards with a trackball, the IP protection of the operator station is reduced to IP54 when the trackball is being moved.
Mechanical data note	The mechanical data apply to an FR enclosure with display and keyboard. They may change accordingly with other enclosure types as well as any additional built-in or added components.

## Mounting / Installation

Enclosure type	Stainless steel enclosure (FR) optional clean room (CFR)
Mounting option	Wall, elbow, stand

## Components

Keyboard	optional, 105 keys with trackball / joystick / touchpad (Ex ia)
----------	---

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.