

8008/2-045 Art. No. 128492



- 2-, 3- or 4-pole control switch: 3-pole load disconnect switch with one auxiliary contact
- Suitable for EMERGENCY STOP functions (according to IEC/EN 60204, DIN VDE 0113)
- Latching and spring return positions possible

MY R. STAHL 8008A



R. STAHL Series 8008 control switches are available as 2-, 3- or 4-pole control switches or 3-pole load disconnect switches with one auxiliary contact. Their positive opening NC contacts also make them suitable for EMERGENCY STOP functions. You can choose the switching function and perform it in the latching or spring return position.

Technical Data

Explosion Protection

| | |
|--------------------------------|---|
| Application range (zones) | 1, 2 |
| IECEX gas certificate | IECEX PTB 06.0010 U |
| IECEX gas certificate | IECEX PTB 06.0010 U |
| IECEX gas explosion protection | Ex db eb IIC T6 |
| ATEX gas certificate | PTB 00 ATEX 1111U |
| ATEX gas certificate | PTB 00 ATEX 1111U |
| ATEX gas explosion protection | Ex II 2 G Ex db eb IIC T6 |
| Marking ULus | Class I, Zone 1 AEx db eb IIC T6 Gb Class I, Div. 2, Groups A,B,C,D |
| Marking cUL | Class I, Zone 1 Ex db eb IIC T6 Gb Class I, Div. 2, Groups A,B,C,D |
| Certificates | ATEX (PTB), Brazil (ULB), Canada / USA (UL), Canada (FM), Canada (UL), China (CQST), IECEX (PTB), Korea (KTL), USA (FM) |

Electrical Data

| | |
|----------------------------------|-------|
| Rated operational voltage AC | 690 V |
| DC rated operational voltage | 230 V |
| Rated operational voltage AC UL | 600 V |
| Rated operational current for AC | 16 A |
| Rated operational current for DC | 0.4 A |
| Rated operational current UL | 6 A |
| No. of poles | 2 |
| Switching angle | 90 ° |

Ambient Conditions

| | |
|---------------------|-------------------|
| Ambient temperature | -50 °C ... +60 °C |
|---------------------|-------------------|

Mechanical Data

| | |
|---------------------------|-------------|
| Degree of protection (IP) | IP00 |
| Enclosure material | Epoxy resin |

8008/2-045 Art. No. 128492


Mechanical Data

| | |
|--------------------------------|---------------------|
| Contact material | Silver-nickel |
| Connection cross-section | 2.5 mm ² |
| Number of switching positions | 2 |
| Assembly for swit. arrangement | 045 |
| Weight | 128 g |
| Weight | 0.28 lb |



Mounting / Installation

| | |
|-------------------------------------|--------|
| Tightening torque | 1.8 Nm |
| Max. USA solid connection terminals | 14 AWG |

Technical Drawings – Subject to Alterations



Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



8008/2-0 1- or 2-pole control switch

Accessories

Rotary actuator, small, lockable

| | | Art. No. |
|--|--|----------|
| | Ø39, can be locked with one lock, 45° position with standard seal for up to -20 °C | 227391 |
| | Ø39, can be locked with one lock, 90° position with standard seal for up to -20 °C | 227359 |
| | Diameter 39 mm, lockable using 1 lock, 45° position Seal: Silicone, up to -60 ° | 227392 |

8008/2-045 Art. No. 128492

Rotary actuator, small, lockable

ASSY734

Art. No.



Diameter 39 mm, lockable using 1 lock, 90° position
Seal: Silicone, up to -60 °

227360

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.