

8544/1-32 Art. No. 171154



- 3-pole and 3-pole+N load disconnect switch with isolating characteristics according to IEC/EN 60947-4
- Retrofittable: Pick-off terminal block, auxiliary contacts, Ex i isolating element, N terminal, PE terminal, parallel drive, adaptor plate for connecting cable lugs
- Auxiliary contacts with delayed, leading or synchronising switching function

MY R. STAHL 8544A



R. STAHL Series 8544 load and motor switches are used as Ex d load disconnect switches: They isolate and switch electric circuits in hazardous areas. They can also be used in non-hazardous areas. The innovative switch concept boasts simple, clear connections and a state-of-the-art contact system. A variety of terminals and contacts can be retrofitted.

Technical Data

Explosion Protection

Application range (zones)	1, 2, 21, 22
IECEX gas certificate	IECEX PTB 09.0011 U
IECEX gas explosion protection	Ex db eb IIC T6
ATEX gas certificate	PTB 08 ATEX 1060 U
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC T6
Certificates	ATEX (PTB), Brazil (ULB), Canada (FM), China (CQST), IECEX (PTB), USA (FM)

Electrical Data

Rated operational voltage AC	690 V
Rated operational current	80 A
Short-circuit strength	20 kA
Max. short-circuit protection	160 A
Tripping characteristic	gG

Auxiliary Power

Max. power dissipation	3.8 W
------------------------	-------

Ambient Conditions

Ambient temperature	-50 °C ... +80 °C
---------------------	-------------------

Mechanical Data

Degree of protection (IP)	IP20
Enclosure material	Polyamide / epoxy resin
Contact material	Silver stannic oxide
Connection terminal, stranded max.	50 mm ²
Min. auxiliary contact connection terminals	1,5 mm ²
Max. auxiliary connection connection terminals, finely stranded	2,5 mm ²
Connection cross-section	50 mm ²
Connection cross section min.	6 mm ²

8544/1-32 Art. No. 171154

Mechanical Data


Max. connection cross section, solid	10 mm ²
Max. connection cross-section, finely stranded	50 mm ²
Service life, min.	10 ⁴ operating cycles
Detailed number of poles	3 P
Weight	4.85 lb

Mounting / Installation

Connection type	Screw terminal
-----------------	----------------


Technical Drawings – Subject to Alterations

0°	1	3	5
90°	X	X	X
	2	4	6



8544/1-3 and 8549/1-3, 3-pole main contacts

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



8544/1-3, 3-pole

Dimension A: 191.7 mm
 Assembly kit: 8544A0303-3
 Selector shaft: 111 mm
 Installation in enclosure: 8146/...5 and 8150/.....-190

Dimension A: 151.7 mm
 Assembly kit: 8544A0303-2
 Selector shaft: 71 mm
 Installation in enclosure: 8146/...3 and 8150/.....-150


Dimension A: 132.7 mm
 Assembly kit: 8544A0303-1
 Selector shaft: 52 mm
 Installation in enclosure: 8146/...2


Accessories

Auxiliary contact

Art. No.


8544/1-32 Art. No. 171154


	2 NC (8080/1-3) 250 V AC/DC Max. 6 A 1.5 to 2.5 mm ² , solid/finely stranded The switching function of the auxiliary contact depends on the installation slot used. Left and right: Synchronising	168356
	1 NC + 1 NO (8080/1-1) 250 V AC/DC Max. 6 A 1.5 to 2.5 mm ² , solid/finely stranded The switching function of the auxiliary contact depends on the installation slot used. Left: Delayed (ON), leading (OFF) Right: Synchronising	168351
	2 NO (8080/1-4) 250 V AC/DC Max. 6 A 1.5 to 2.5 mm ² , solid/finely stranded The switching function of the auxiliary contact depends on the installation slot used. Left and right: Synchronising	168353


Insertion prism		Art. No.
	for connecting conductors with cross-sections $\leq 10 \text{ mm}^2$ (single conductor connection) or $\leq 6 \text{ mm}^2$ (multiple conductor connection) at the main terminals	171324

Spare Parts






Auxiliary contact key		Art. No.
	For removing installed auxiliary contacts	201909

Connection for cable lug		Art. No.
	Assembly kit for connecting conductors with cable lug	171292

Ex i isolating element		Art. No.
	for ensuring the required 50 mm tight string length between the connection points of intrinsically safe and non-intrinsically safe circuits	169683

Parallel drive		Art. No.
	for actuating two combined load and motor switches at the same time	171330


8544/1-32 Art. No. 171154

PE/N terminal		Art. No.
	for retrofitting	168347
Pick-off terminal block		Art. No.
	Pick-off terminal block 10-UKH 50	168543
Rotary actuator		Art. No.
	Dia. 122.5; lockable in 0-position with max. three padlocks 8604C1-2-1-1-01-1-2 Handle: Black Protective collar: Black Designation plate: 0/OFF – I/ON	201436
	Dia. 122.5; lockable in 0-position with max. three padlocks 8604C1-2-1-1-01-2-2 Handle: Red Protective collar: Yellow Designation plate: 0/OFF – I/ON	201437
	Dia. 122.5; lockable in 0-position with max. three padlocks 8604C1-2-1-1-01-3-2 Handle: Red Protective collar: Black Designation plate: 0/OFF – I/ON	201438
Rotary actuator for 6-pole safety switch		Art. No.
	Dia. 180 mm; lockable in 0-position with max. three padlocks Cover can only be removed in I/ON position. 8604C1-3-2-1-01-1-1 Handle: Black Protective collar: Black Designation plate: 0/OFF – I/ON	201459
Rotary actuator for 6-pole switch		Art. No.
	Dia. 180; lockable in 0-position with max. three padlocks 8604C1-3-1-1-01-1-1 Handle: Black Protective collar: Black Designation plate: 0/OFF – I/ON	201454
	Dia. 180; lockable in 0-position with max. three padlocks 8604C1-3-1-1-01-3-1 Handle: Red Protective collar: Black Designation plate: 0/OFF – I/ON	201457

8544/1-32 Art. No. 171154

Rotary actuator for safety switch

Art. No.



Dia. 122.5; lockable in 0-position with max. three padlocks
Cover can only be removed in I/ON position.
8604C1-2-2-1-01-1-2
Handle: Black
Protective collar: Black
Designation plate: 0/OFF – I/ON

201439

Dia. 122.5; lockable in 0-position with max. three padlocks
Cover can only be removed in I/ON position.
8604C1-2-2-1-01-2-2
Handle: Red
Protective collar: Yellow
Designation plate: 0/OFF – I/ON

201451

Selector shaft

Art. No.



52 mm for 8146/...2

168354

71 mm for 8146/...3 or 8150/-.....-150

168355

111 mm for 8146/...5 or 8150/-.....-190

168357

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.