

CMP-63sTE1FU Art. No. 243502



- Ex d and Ex e cable gland for armoured cables with SWA, wire-braid and tape armouring made of steel and aluminium
- Prevention of cold flow
- Compensating displacement seal (CDS), flood seal with integral protection, controlled outer load retention seal
- Internationally certified in accordance with IECEx, ATEX and cCSAus, EMC-tested

MY R. STAHL TE1FUA



The Series TE1FU metal Ex d and Ex e cable glands are suitable for all types of armoured cables, i.e. for SWA, wire-braid and tape armouring made of steel and aluminium. They have a multifunctional holder for the armouring and various seals. They are also designed to prevent cold flow and are EMC-tested. Their auxiliary functions and the sequential, three-stage installation offer increased safety and reduce the amount of time, costs and risks involved in installation.

Technical Data


| Explosion Protection | |
|--|--|
| Ex version | Ex e & Ex d & Ex nR & Ex ta |
| Application range (zones) | 1, 2, 20, 21, 22 |
| IECEX gas certificate | IECEX CML 18.0183X |
| IECEX gas explosion protection | Ex db IIC Gb |
| IECEX dust certificate | IECEX CML 18.0183X |
| IECEX dust explosion protection | Ex ta IIIC Da |
| IECEX firedamp certificate | IECEX SIM 14.0007 X |
| IECEX firedamp protection | Ex db I Mb |
| IECEX firedamp protection 2 | Ex eb I Mb |
| IECEX restricted breathing certificate | IECEX CML 18.0183X |
| IECEX restricted breathing | Ex nR IIC Gc |
| ATEX gas certificate | CML 18ATEX1326X |
| ATEX gas explosion protection | Ex II 2 G Ex db IIC Gb |
| ATEX dust certificate | CML 18ATEX1326X |
| ATEX dust explosion protection | Ex II 1 D Ex ta IIIC Da |
| ATEX firedamp certificate | CML 18ATEX1326X |
| ATEX firedamp protection | Ex I M2 Ex db I Mb |
| ATEX firedamp protection 2 | Ex I M2 Ex eb I Mb |
| ATEX restricted breathing certificate | CML 18ATEX4318X |
| ATEX restricted breathing | Ex II 3 G Ex nR IIC Gc |
| Notes | The product certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com) |
| Ambient Conditions | |
| Ambient temperature | -60 °C ... +130 °C |
| Mechanical Data | |
| Version | 63s |

CMP-63sTE1FU Art. No. 243502

Mechanical Data

| | |
|---------------------------|---|
| Strain relief | No |
| Degree of protection (IP) | IP66 |
| Degree of protection note | IP67 and IP68 mounting according to the specifications of the manufacturer, CMP. The specified degrees of protection are only fulfilled if CMP installation accessories are used. |
| Sealing material | SOLO LSF |
| Sealing ring material | Viton |
| Material | Stainless steel |
| Silicone-free | Yes |
| Clamping range | 45.6 – 59.4 mm |
| Armouring type | All armouring |
| Armouring type 2 | Without lead sheath |
| Armouring type 3 | With double seal |
| Clamping range | 45.6 ... 59.4 mm |
| Construction type | BS 6121, IEC/EN 62444 |
| Width across corners | 82.4 mm |
| Width across flats | 75 mm |
| Thread size | M63 |
| Thread length | 15 mm |
| Thread pitch | 1,5 |
| Thread standard | metric |
| Gland size | 63s |
| Grooved cone | 0.6 ... 1.6 mm |
| Stepped cone | 2 ... 2.5 mm |
| Inner sheath | 40.1 ... 49.9 mm |
| Outer sheath | 45.6 ... 59.4 mm |
| Protrusion length | 90.5 mm |
| Impact strength | 20 J |
| PVC boot | PVC23 |
| Lot size | 1 |
| Weight | 1.5 kg |
| Weight | 3.31 lb |

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



A = Inner sheath
 B = Outer sheath
 C = Thread size
 D = Width across corners
 D = Width across flats
 E = Thread length
 F = Protrusion length

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.