Installation equipment and accessories

Stopping plug With hex head



CMP-757-D-M2-4 Art. No. 251101



- Metal Ex d and Ex e stopping plugs
- · Wide selection of thread types and sizes
- Operating temperature range -60 °C to +200 °C
- · Global certification, IECEx, ATEX, cCSAus and UL

MY R. STAHL 757DA



Series 757 metal Ex d and Ex e stopping plugs with hexagon insert bit and head make it possible to temporarily or permanently seal unused drilled holes. There is a wide selection of different thread sizes and types available for this. They have global certification according to IECEx, ATEX, UL and cCSAus.

Technical Data

| Explosion Protection | |
|--------------------------------|---|
| Application range (zones) | 1, 2, 20, 21, 22 |
| IECEx gas certificate | IECEx CML 18.0177X |
| IECEx gas explosion protection | Ex db IIC Gb |
| IECEX firedamp certificate | IECEx CML 18.0177X |
| IECEx firedamp protection | Ex db I Mb |
| IECEx firedamp protection 2 | Ex eb I Mb |
| ATEX gas certificate | CML 18ATEX1320X |
| ATEX gas explosion protection | |
| ATEX firedamp certificate | CML 18ATEX1320X |
| ATEX firedamp protection | □ M2 Ex db I Mb |
| ATEX firedamp protection 2 | □ M2 Ex eb I Mb |
| Notes | The product certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com) |
| Ambient Conditions | |
| Ambient temperature | -60 °C +200 °C |
| Mechanical Data | |
| Degree of protection (IP) | IP66 |
| Degree of protection note | IP67 and IP68 mounting according to the specifications of the manufacturer, CMP. The specified degrees of protection are only fulfilled if CMP installation accessories are used. |
| Degree of protection (IP) UL | IP66 |
| Silicone-free | Yes |
| Drive | External hexagon |
| Width across corners | 26.4 mm |
| Width across flats | 24 mm |
| Outer diameter | 26.4 mm |
| Thread size | M20 |
| Thread length | 15 mm |

Installation equipment and accessories


Stopping plug With hex head



CMP-757-D-M2-4 Art. No. 251101

| Mechanical Data | |
|-----------------------------|---------|
| Thread pitch | 1,5 |
| Impact strength (IEC 62262) | IK10 |
| Packaging unit | 1 |
| Weight | 0.17 lb |

Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations



A = Thread size

- B = Length L = Thread length D = Outer diameter
- b = Dimension b
- d = Dimension d
- E = Width across corners
- SW = Hexagon socket width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.