

IDM264-BT-Z1 Art. No. 310745



- Certified acc. to ATEX and IECEx for hazardous Zones 1, 2, 21, 22
- Wired or wireless Bluetooth scanners
- 1D / 2D barcodes, stacked codes
- Scanner compatible with R. STAHL's ORCA, SHARK, MANTA, EAGLE and RAPTOR HMI device platforms

MY R. STAHL IDMEXA



R. STAHL's IDM barcode scanners are ATEX and IECEx certified for hazardous zones 1, 2, 21 and 22.

Depending on the scanner, all common 1D / 2D barcodes and stacked codes can be read. The reading process is confirmed acoustically with a beep, visually with LED and with vibration. The explosion-protected HMI devices are all-round designed to meet industrial requirements: their compact enclosure with IP65 is extremely robust - it can withstand up to 50 drops onto concrete from a height of 2 m.

The wired scanners support all common cable interfaces, and, when required, the cables can be replaced without the need for any tools. The wireless Bluetooth scanners transmit all data via Bluetooth.

Technical Data

General

| | |
|----------------------|--|
| Special version | Bluetooth wireless scanner |
| Version | two-dimensional imager scanner |
| Barcode types | one- and two-dimensional 1D and 2D (barcode and stacked code) (PDF417) |
| Base loading station | IDMx64-BT-Base-Z1 IDMx64-BT-Base (Non-Ex) |
| WebCode | IDMEXA |

Explosion Protection

| | |
|---------------------------|---|
| Ex version | Yes |
| Application range (zones) | 1 & 2, 21 & 22 |
| Scope | EU (CE / ATEX) International (IECEx) |

Electrical Data

| | |
|----------------------------------|--------------------------|
| DC rated operational voltage | 3.6 V |
| Light source | Visible red light, 630nm |
| Resistance to light interference | 100 000 lx |

Auxiliary Power

| | |
|--------------|-------------|
| Power supply | Via battery |
|--------------|-------------|

Ambient Conditions

| | |
|---------------------|---|
| Ambient temperature | -20°C ... +50°C |
| Storage temperature | -30°C ... +70°C |
| Relative humidity | ±95 % , non-condensing |
| Shock resistance | 50 drops from a height of 2 m onto a concrete surface |

IDM264-BT-Z1 Art. No. 310745

Mechanical Data

| | |
|--------------------------------------|-------------------------|
| Front enclosure protection type (IP) | IP65 |
| Rear enclosure protection type (IP) | IP65 |
| Enclosure material | Plastic |
| Width | 104 mm |
| Height | 185 mm |
| Depth | 76 mm |
| Dimensions (WxHxD) | 104 mm x 185 mm x 76 mm |
| Weight | 0.44 lb |

Accessories

| Adapter Cable | | Art. No. |
|-----------------------|--|----------|
| | VB-IDMx6x-SOCKET-RS232-0.5m Adapter cable for IDMx6x scanner, display xx8 <--> IDMx6x connection cable, open ends to binder coupling for interface RSi-232 (xx8), cable length: 0.5 m straight | 254452 |
| Base stations scanner | | Art. No. |
| | IDMx61-Base-A Base station for handheld scanner IDMx61-BT, no Bluetooth, Non-Ex, wireless loading station, loading in safe area | 275761 |
| | IDMx64-Base-A Base station for handheld scanner IDMx64-BT, Bluetooth, Non-Ex, wireless loading station, loading in safe area | 310747 |
| | IDMx64-BT-Base-Z1 Base station for handheld scanner IDMx64-BT, Bluetooth, Zone 1, wireless access and loading station, loading in Zone 1 | 310746 |
| Battery | | Art. No. |
| | IDMx6x-BT-ex-LionX Replacement battery (Li ions) for IDMx6x-BT-ex | 283128 |

IDM264-BT-Z1 Art. No. 310745

| Connection Cable | Art. No. |
|--|----------|
| VB-IDM160-RS232-SR-1.8m Connection cable for IDM160, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V cable length 1.8 m, straight, Binder plug | 224085 |
| VB-IDM160-RS232-SR-3.6m Connection cable for IDM160, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V cable length 3.6 m, coiled, Binder plug | 224086 |
| VB-IDMx60-RS232-1.8m Connection cable for IDM160 / IDM260, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug | 224081 |
| VB-IDMx60-RS232-3.6m Connection cable for IDM160 / IDM260, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug | 224082 |
| VB-IDMx60-USB-1.8m Connection cable for IDM160, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug | 224083 |
| VB-IDMx60-USB-3.6m Connection cable for IDM160, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug | 224084 |
| VB-IDMx6x-Base-RS232-SR-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug | 224102 |
| VB-IDMx6x-Base-RS232-SR-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug | 224103 |
| VB-IDMx6x-Base-VM-RS232-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug | 224100 |
| VB-IDMx6x-Base-VM-RS232-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug | 224101 |
| VB-IDMx6x-Base-VM-USB-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug | 224104 |
| VB-IDMx6x-Base-VM-USB-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug | 224105 |

IDM264-BT-Z1 Art. No. 310745

| Connection Cable Extension | | Art. No. |
|--|--|-----------------|
| VB-IDMx6x-EXT-3.0m-Z1 Extension cable for IDMx6x zone 1, cable length 3 m, straight | | 265948 |
| VB-IDMx6x-EXT-3.0m-Z1-spiral Extension cable for IDMx6x zone 1, cable length 3 m, coiled | | 263908 |
| VB-IDMx6x-EXT-6m-Z1 Extension cable for IDMx6x zone 1, cable length: 6 m, straight | | 224108 |
| VB-IDMx6x-EXT-6.0m-Z1-spiral Extension cable for IDMx6x zone 1, cable length 6 m, coiled | | 265949 |
| Power supply | | Art. No. |
| DSP-IDMx6x-DC5V Power supply for non-ex base loading station | | 224095 |

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.