## Installation equipment and accessories

## Stopping plug With hex head



### CMP-757-D-M4-5 Art. No. 253027



- Metal Ex d and Ex e stopping plugs
- · Wide selection of thread types and sizes
- Operating temperature range -60 °C to +200 °C
- · Global certification, IECEx, ATEX, cCSAus and UL

### MY R. STAHL 757DA



Series 757 metal Ex d and Ex e stopping plugs with hexagon insert bit and head make it possible to temporarily or permanently seal unused drilled holes. There is a wide selection of different thread sizes and types available for this. They have global certification according to IECEx, ATEX, UL and cCSAus.

### **Technical Data**

Explosion Protection	
Application range (zones)	1, 2, 20, 21, 22
IECEx gas certificate	IECEx CML 18.0177X
IECEx gas explosion protection	Ex db IIC Gb
IECEX firedamp certificate	IECEx CML 18.0177X
IECEx firedamp protection	Ex db I Mb
IECEx firedamp protection 2	Ex eb I Mb
ATEX gas certificate	CML 18ATEX1320X
ATEX gas explosion protection	
ATEX firedamp certificate	CML 18ATEX1320X
ATEX firedamp protection	□ M2 Ex db I Mb
ATEX firedamp protection 2	□ M2 Ex eb I Mb
Notes	The product certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com)
Ambient Conditions	
Ambient temperature	-60 °C +200 °C
Mechanical Data	
Degree of protection (IP)	IP66
Degree of protection note	IP67 and IP68 mounting according to the specifications of the manufacturer, CMP. The specified degrees of protection are only fulfilled if CMP installation accessories are used.
Degree of protection (IP) UL	IP66
Silicone-free	Yes
Drive	External hexagon
Width across corners	39.6 mm
Width across flats	36 mm
Outer diameter	39.6 mm
Thread size	M32
Thread length	15 mm

# Installation equipment and accessories


# Stopping plug With hex head



#### CMP-757-D-M4-5 Art. No. 253027

Mechanical Data	
Thread pitch	1,5
Impact strength (IEC 62262)	IK10
Packaging unit	1
Weight	0.42 lb

#### Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations



A = Thread size

B = Length L = Thread length D = Outer diameter

b = Dimension b

d = Dimension d

E = Width across corners

SW = Hexagon socket width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.