

### IS530.2 Smartphone Set ROW noCamera Art. No. 317279



- No camera
- universal, 13-pin ISM (multifunction) interface for connection of additional devices for many applications
- Android Enterprise Recommended
- zero touch capable
- MDM compatible

#### MY R. STAHL MPHONEA



With its ISM interface, the powerful, explosion-protected industrial smartphone has many applications. Other additional modules such as an RSM, PTT headsets, the professional IS-TH1xx.1 barcode scanner and the IS-TC1A.1 thermal imaging camera make the IS530.1 smartphone a high-performance, multifunctional device. The smartphones are Android Enterprise Recommended, zero touch capable and MDM compatible.

### Technical Data

General	
Technology	Telephone
Version	Smartphone
Explosion Protection	
Application range (zones)	2, 22
Application range	Zone 2, Zone 22
Scope	EU (CE / ATEX) Global (IECEX) United Kingdom (UKCA) China (PCEC) South Africa (SANS) Australia (RCM) Saudi Arabia (SASO) United Arab Emirates (UAE) Mexico (MX)
IECEX certification	EPS 19.0033X
ATEX certification	EPS 19 ATEX 1 070 X
PCEC certification	CE20.2418X
SANS certification	MTEEx-S/22.0568 X
IECEX gas explosion protection	Ex ic IIC T4 Gc IP64
IECEX dust explosion protection	Ex ic IIIC T135°C Dc IP64
ATEX gas explosion protection	Ex ic II 3G Ex ic IIC T4 Gc IP64
ATEX dust explosion protection	Ex ic II 3D Ex ic IIIC T135°C Dc IP64
PCEC gas explosion protection	Ex ic IIC T4 Gc
PCEC dust explosion protection	Ex ibD 21 T135°C
SANS gas explosion protection	Ex ic IIC T4 Gc IP64
SANS dust explosion protection	Ex ic IIIC T135°C Dc IP64

### IS530.2 Smartphone Set ROW noCamera Art. No. 317279

#### Electrical Data

Processor type	Qualcomm SDM660 Octa-core
Main memory	4 GB
Data memory	64 GB int. + SD up to 128 GB
Operating system	Android 10 (upgr. 13)
Mobile standard	2G, 3G, 4G
Interface medium	WiFi 802.11 a/b/g/n/ac/e/k/r/h
Optional interface 1	Bluetooth 5
SD card type/size	MicroSD/up to 128 GB
SIM card number	Double SIM
SIM card size	Micro

#### Display

Display size in inches	4.50
Display size in cm	11.43
Display resolution	FWVGA
Touch screen	Capacitive
Touchscreen material	Gorilla glass corning 3rd gen.
Backlight	LED technology

#### Ambient Conditions

Ambient temperature	-20 – 60
---------------------	----------

#### Mechanical Data

Degree of protection (IP)	IP68
MIL-standard	810G (h/l temp., shock, vibr.)
Width	80 mm
Height	155 mm
Depth	25 mm
Weight	0.72 lb

#### Included in delivery

- > Smartphone with integrated battery
- > Universal power adapter
- > i.safe PROTECTOR 2.0
- > i.safe PROTECTOR 3.0
- > Screwdriver
- > Screen protector
- > Safety regulations
- > Quick Start Guide

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.