

## Signalling devices

Audible/visual signalling device Horn/XENON light fitting

In flameproof enclosure

YL60/324-PS101-00BW30-ST000-0000 Art. No. 319411

STAHL



- The latest generation of audible and visual alarm devices
- Ex d/Ex e connection chambers
- Visual solutions with 5 to 21 J XENON and high-power LEDs with various light modes and 4 light channels
- Audible solutions with directional or omnidirectional horn with up to 120 dB(A) at 1 m, 4 tone channels and 64 preconfigured tones
- Four output levels can be configured
- Brackets, fixings and protective grid made from stainless steel
- Compliant with EN 54/DNV
- Fastening bracket and protective cage included

MY R. STAHL YL60C



The **YL60/3 product series** provides audible and visual alarm signals which can be used to alert, warn or draw attention to equipment malfunction/start-up or any number of safety-related issues in hazardous areas. The preconfigured signal tones and light patterns (LED) provide a wide range of internationally standardised signal patterns. The audible and visual signals can be operated separately or in combination, with four channels available for each type of signal, enabling flexible use. The signalling devices meet the requirements of EN 54 and DNV for extremely challenging ambient conditions.

### Technical Data

#### Explosion Protection

|                                 |                                                  |
|---------------------------------|--------------------------------------------------|
| Area of application             | European Union (ATEX)<br>IECEX<br>United Kingdom |
| Application range (zones)       | 1, 2, 21, 22                                     |
| IECEX gas certificate           | IECEX EPS 22.0046X                               |
| IECEX gas explosion protection  | Ex db eb IIC T4 Gb                               |
| IECEX dust certificate          | IECEX EPS 22.0046X                               |
| IECEX dust explosion protection | Ex tb IIIC T100 °C Db                            |
| ATEX gas certificate            | EPS 22 ATEX 1 224X                               |
| ATEX gas explosion protection   | II 2 G Ex db eb IIC T4 Gb                        |
| ATEX dust certificate           | EPS 22 ATEX 1 224X                               |
| ATEX dust explosion protection  | II 2 D Ex tb IIIC T100 °C Db                     |
| Certificates                    | ATEX (BVIS), IECEX (BVIS)                        |
| Declaration of conformity       | ATEX (EUK)                                       |

#### Electrical Data

|                              |               |
|------------------------------|---------------|
| Rated operational voltage AC | 110 ... 240 V |
| Rated operational voltage DC | 133 ... 272 V |
| Line monitoring              | Yes           |
| Tolerance                    | -10 ... 10 %  |

#### Acoustic Data

|                      |                           |
|----------------------|---------------------------|
| Horn version         | omnidirectional           |
| Sound pressure level | max. 114 dB(A) @ 1 m      |
| Sound level          | 4                         |
| Volume control       | Max. -18 dB(A) adjustment |

# Signalling devices

Audible/visual signalling device Horn/XENON light fitting

In flameproof enclosure

YL60/324-PS101-00BW30-ST000-0000 Art. No. 319411

## Lighting Data

|                                               |                       |
|-----------------------------------------------|-----------------------|
| Lamp                                          | 5 J xenon flash tubes |
| Effective luminous intensity (1 Hz, flashing) | 25 cd                 |

## Ambient Conditions

|                     |                       |
|---------------------|-----------------------|
| Ambient temperature | -40 °C ... 70 °C (T4) |
| Storage temperature | -60 °C ... 70 °C      |

## Mechanical Data

|                                           |                                              |
|-------------------------------------------|----------------------------------------------|
| IP degree of protection (IEC 60598)       | IP66                                         |
| Connection chamber version                | Ex e                                         |
| Enclosure material                        | Aluminium, powder-coated, Seawater-resistant |
| Enclosure colour                          | red, similar to RAL 3020                     |
| Silicone-free content                     | Contains silicone                            |
| Trumpet material                          | PC/PBT                                       |
| Material dome                             | Polycarbonate, prismatic                     |
| Protective collar material                | Polycarbonate (PC cover)                     |
| Wire guard material                       | Stainless steel                              |
| Max. solid connection terminals           | 4 mm <sup>2</sup>                            |
| Max. finely stranded connection terminals | 2.5 mm <sup>2</sup>                          |
| Width                                     | 176 mm                                       |
| Height                                    | 422 mm                                       |
| Length                                    | 128 mm                                       |
| Lens colour                               | Blue                                         |
| Mounting                                  | L-bracket                                    |
| Weight                                    | 6.72 kg                                      |
| Weight                                    | 14.81 lb                                     |

## Mounting / Installation

|                        |                 |
|------------------------|-----------------|
| Connection type        | Push in         |
| Mounting part material | Stainless steel |

## Components

|                          |                                                |
|--------------------------|------------------------------------------------|
| Drilled holes            | 2 x M20 + 2 x M25                              |
| Cable glands and entries | 1 x M20 Ø 4 ... 13 mm<br>1 x M25 Ø 7 ... 17 mm |
| Material cable gland     | Polyamide, black                               |
| Stopping plugs           | 2x M20 + 2x M25                                |
| Stopping plug material   | Polyamide, black                               |

# Signalling devices

STAHL

Audible/visual signalling device Horn/XENON light fitting

In flameproof enclosure

YL60/324-PS101-00BW30-ST000-0000 Art. No. 319411

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



YL60/3 omnidirectional horn

## Accessories

| Metal cable gland                                                                  |                                                                                                                                                                                | Art. No. |
|------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
|  | Ex d and Ex e cable gland with compound for all types of armoured cables (SWA, wire-braid, tape) (nickel-plated brass)<br>Type 20PX2K, M20 x 1.5                               | 109428   |
|                                                                                    | Ex d and Ex e cable glands with RapidEx sealing system for all types of unarmoured cables and wire-braid-armoured cables (nickel-plated brass)<br>Type 20PX2K-REX, M20 x 1.5   | 246649   |
|  | Ex d and Ex e cable glands with compound for all types of unarmoured cables and wire-braid-armoured cables (nickel-plated brass)<br>Type 20PXSS2K, M20 x 1.5                   | 109441   |
|                                                                                    | Ex d and Ex e cable glands with RapidEx sealing system for all types of unarmoured cables and wire-braid-armoured cables (nickel-plated brass)<br>Type 20PXSS2K-REX, M20 x 1.5 | 246605   |
| Plastic cable gland                                                                |                                                                                                                                                                                | Art. No. |
|  | 8161/7-M20-1304, Ex e<br>Polyamide, M20 x 1,5 mm, 4 – 13 mm<br>Lot size 50 pieces                                                                                              | 239156   |
| Stopping plug                                                                      |                                                                                                                                                                                | Art. No. |
|  | 8290/3-M20<br>Plastic, M20 x 1.5<br>Lot size 1 piece                                                                                                                           | 143522   |
|                                                                                    | 8290/3-M20<br>Plastic, M20 x 1.5<br>Lot size 100 pieces                                                                                                                        | 285773   |

## Signalling devices

**STAHL**

Audible/visual signalling device Horn/XENON light fitting

In flameproof enclosure

YL60/324-PS101-00BW30-ST000-0000 Art. No. 319411

### Spare Parts

#### Mounting accessories

#### Art. No.



L-bracket, stainless steel 1.4404

319271



U-bracket, stainless steel 1.4404

319280

#### Protective cage

#### Art. No.



Protective cage, stainless steel 1.4404

319272

#### Textured lens

#### Art. No.



blue

319274

#### Lamp

#### Art. No.



Xenon tube PCB 5 joules

319281

#### Shaped horn

#### Art. No.



omnidirectional, repair kit

319250

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.