## Components for system solutions

Empty enclosure Screw-on cover

8151/0-113A-3311 Art. No. 324615





- · Ex e enclosure series made of stainless steel
- Ideally suited for terminal boxes
- · 14 different standard sizes
- · Cover with screws or with hinge
- Available as Ex e empty enclosure or customised as Ex e terminal box

### MY R. STAHL 8151A



Ex e enclosure made of high-quality 1.4404 stainless steel, specially designed for use as a terminal box. 14 standard sizes with 1 mm/1.2mm thickness, optionally with screw-on cover or hinge with screws or cam locks, offer great flexibility for a wide range of applications. Can be customised with terminal blocks from various manufacturers, as well as a large selection of cable glands, cable entries, mounting and flange plates.


The enclosures in the 8151 series are available as empty enclosures with U-certification or as fully certified Ex e terminal boxes.

#### **Technical Data**

Explosion Protection	
Area of application	European Union (ATEX) IECEx
Application range (zones)	1, 2, 21, 22
IECEx gas certificate	IECEx BVS 24.0002 U
IECEx gas explosion protection	Ex eb IIC Gb
IECEx dust certificate	IECEx BVS 24.0002 U
IECEx dust explosion protection	Ex tb IIIC Db
ATEX gas certificate	BVS 24 ATEX E 001 U
ATEX gas explosion protection	
ATEX dust certificate	BVS 24 ATEX E 001 U
ATEX dust explosion protection	
Certificates	ATEX (BVS), IECEx (BVS)
Ambient Conditions	
Ambient temperature	-60 °C +135 °C
Ambient temperature	-76 °F +275 °F
Mechanical Data	
Degree of protection (IP) (IEC 60529)	IP66
Enclosure material	Stainless steel 1.4404, Brush finished
Silicone-free	No
Cover	Screw-on cover
Cover fixing type	With captive screws
Cover thickness	1.2 mm
Cover thickness in inches	0.0047 in
Wall thickness	1.2 mm

# **Components for system solutions**

Art. No. 324615







				-	
- IV	ואמו	nar	บเกลไ	Data	2

8151/0-113A-3311


Wednamear Data	
Wall thickness in inches	0.0047 in
Width	400 mm
Width, inches	15.75 in
Height	600 mm
Height in inches	23.62 in
Depth	150 mm
Depth in inches	5.9 in
Impact strength (IEC 60079)	7 J
Impact strength (IEC 62262)	IK09
Packaging unit	1
Weight	8.7 kg
Weight	19.18 lb
Mounting / Installation	
Tightening torque of cover screw 1	4.5 N · m
Tightening torque of cover screw 1 lbf in	39.83 lbf in

#### Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations





Mounting bracket top



We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.