



- DIN rail mounting.
- 4 or 8 output circuits.
- 2-pole switching. Both poles fused.
- For connection of LED navigation and signal lights. Threshold current value: 34mA.
- Connected LED light must have built in life time control.
- Connected LED light must be selfmonitored and if a failure arise, current must be reduced to <31mA.
- Lamp circuits galvanic isolated from control circuit
- Local emergency switches for control of outputs.
- Connections for main and emergency supply to output circuits.
- Built-in snubber network which allows termination of a wide range of communication cable, 100-250 Ohm characteristic impedance. End resistors shall not be used.
- Current detection can be disabled on any circuit if a particular system does not require this feature.

MY R. STAHL T4900D



Designed for control and monitoring of LED navigation and signal lights. Delivered for 4 or 8 output circuits, 24V.

Technical Data

Electrical Data

DC rated operational voltage	18 ... 32 V
DC supply voltage	24 V
Number of RS-485 interfaces	2

Diagnostics

Communication	RS-485
---------------	--------


Ambient Conditions

Ambient temperature	-5 – 70 °C
---------------------	------------


Mechanical Data

Degree of protection (IP)	IP20
Number of buttons	0
Weight	460 g
Weight	1.01 lb

Technical Drawings – Subject to Alterations



Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



490A102501_Rev. A

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.