TRANBERG Solutions

Navigation lights LED Panel Max 21 buttons Max 16 Outputs TEF4800111 Art. No. 332587







- Customer specified texts on panel.
- The system is applicable to both LED and incandescent lamps.
- Up to 10 pcs. 24 VDC (max. 40 W) incandescent lamps or 16 pcs. LED lamps.
- Connections for main and emergency supply to output circuits
- · Can be expanded with a secondary controller.

MY R. STAHL T4800A



Control and monitoring system for navigation and signal lights. Delivered for up to 16 output circuits, 24 VDC. TRANBERG® operator panel has a fixed layout of buttons, but allows for customer specified texts. The operator panel has serial communication to the rest of the system. The panel has text in white letters on a black foil, making it easy to read.

Applications:

Complete control and monitoring of several types of critical lights on vessels: Navigation lights, Signal lights, Suez lights, ROV lights and Towing lights.

Technical Data

Electrical Data	
DC supply voltage	24 V
Power consumption	5 W
Number of RS-485 interfaces	1
Diagnostics	'
Communication	RS-485
Display	
Backlight	Dimmable LED
Mechanical Data	
Degree of protection (IP)	IP20
Enclosure material	Aluminium
Number of buttons	21
Size	1
Mounting cut-out width	180 mm
Mounting cut-out height	205 mm
Weight	4 kg
Weight	8.82 lb

TRANBERG Solutions


TEF4800111





Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations

Art. No. 332587



Size 1 Cut-out 180 mm x 205 mm Size 2 Cut-out 220 mm x 205 mm

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.