

EC-940-AFZ-HDI-O6H-R1 Art. No. 266898



- Ethernet copper connection, PoE++ power supply
- Ex e connection box for easy installation
- Modern IP camera with ONVIF protocol (Profile S) and Full HD
- Day / night - functionality
- Certified acc. to ATEX and IECEx

MY R. STAHL EC940AFZA



The R. STAHL's EC-940-AFZ zoom camera has an Ex e connection box, making installation in hazardous areas especially easy. This camera is equipped with a Ethernet copper connection. The power supply for this camera is via PoE ++ (Power over Ethernet) and the R. STAHL PoE ++ Extender is used as a counterpart. It provides clear images even in difficult light - this is ensured by the 32x optical zoom, the WDR image optimisation and the de-fog function, which sharpens contrast in light fog. The camera is integrated into the surveillance system via the ONVIF protocol (Profile S). These robust surveillance camera in an electropolished stainless steel enclosure (316L) is suitable for temperatures ranging from -55 °C and +65 °C and certified acc. to ATEX and IECEx for hazardous areas.

Technical Data

Explosion Protection	
Application range (zones)	1, 2, 21, 22
IECEx gas certificate	PTB 16.0032X
IECEx gas explosion protection	Ex db eb IIC T4 Gb
IECEx dust certificate	PTB 16.0032X
IECEx dust explosion protection	Ex tb eb IIIC 135 °C Db
ATEX gas certificate	16 ATEX 1019X
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC T4 Gb
ATEX dust certificate	16 ATEX 1019X
ATEX dust explosion protection	Ex II 2 D Ex tb eb IIIC 135 °C Db
Electrical Data	
Rated operational voltage AC	
Rated operational voltage DC	
Interfaces	PoE++
Connection	Ethernet port LAN 10/100 T
Camera Data	
Sensor	1/2.8 CMOS
Lens	f = 4.44 (w) to 142.6 mm (t) From F1.6 to F4.4
Viewing angle	62.8° (wide), 2.23° (tele.)
Focus	Automatic focus
Zoom	32x optical
Resolution	Full HD to 320x180 p
Pixel	Approx. 2.38 megapixels
Accuracy of preset positions	0.02 °

EC-940-AFZ-HDI-O6H-R1 Art. No. 266898

Camera Data

Minimum working distance	1500 mm (wide/tele)
Minimum illumination B/W (ICR-ON)	0.03 lx, F1.6, 1/30s, 50 IRE
Minimum illumination color (ICR-OFF)	0.3 lx F1.6, 1/30S, 50 IRE
Number of streams	Multistream 10 profiles
Frame rate (fps)	H.264 max. 60, MJPEG 15 or 30
S/N ratio	50 dB
Back light compensation	Off / BLC
Electronic shutter	2 to 1/12000s
Compression	H.264, MJPEG
De-fog	Off / Auto / Manual
WDR (dynamic range)	120 dB
White balance	ATW, AWC, manual, internal, External, mercury
Wide Dynamik Range	On/Off

Software

Network protocol	ONVIF profile S
Network Configuration	TCP/IPv4-IPv6, UDP/IPv4-IP6, http, NTP, DHCP, QoS, IGMP, Bonjour
Streaming	Unicast / Multicast

Ambient Conditions

Ambient temperature	-40 °C ... +65 °C
---------------------	-------------------

Mechanical Data

Version	Movable viewing angle
Degree of protection (IP)	IP66
Enclosure material	Stainless steel 1.4404
Surface treatment	Electropolished
Cable length	0 m
Integrated wiper	No
Feature	Ex-e compartment
Package weight	0 kg
Weight	16 kg
Weight	35.27 lb

Accessories

Camera multi-cable armoured

Art. No.

	<p>VB-CAM-MULTI-Ethernet-ARM 1 x Ethernet cable 3 x power supplies 2.5 mm² 7 x data cable 0.34 mm² -60 °C ... +80 °C 19.2 ±0.5 mm outer diameter IEC 60332-1 flame-resistant IEC 60754-2 halogen-free DIN 60811-404 oil-resistant NEK 606 mud-resistant Price and weight per m</p>	<p>252571</p>
--	---	---------------

EC-940-AFZ-HDI-O6H-R1 Art. No. 266898

Wall mount		Art. No.
	<p>Wall Bracket EC-940-AFZ Suitable for EC-940-AFZ Material: 316L stainless steel, electropolished Weight: ca. 8 kg Load bearing capacity: max. 40 kg WxH: 200 x 160 x 330 mm</p>	257043
Pole adapter module		Art. No.
	<p>Pole adapter module EC-940-AFZ Suitable for EC-940-AFZ Material: 316L stainless steel, electropolished Weight: ca. 4.7 kg Load bearing capacity: max. 40 kg WxH: 214 x 194 mm For pole diameter 88 ... 150 mm May only be used together with wall bracket EC-940-AFZ type 257043</p>	257047
Corner adapter		Art. No.
	<p>Corner adapter EC-940-AFZ Suitable for EC-940-AFZ series Material: 316L SST, electropolished Load bearing capacity: max. 40 kg WxHxD: 355 x 150 x 211 mm Weight: ca. 3.2 kg May only be used together with wall bracket EC-940-AFZ type 257043</p>	257048
Ceiling holder		Art. No.
	<p>Parapet mounting EC-940-AFZ Suitable for EC-940-AFZ Material: 316L stainless steel, electropolished Weight: ca. 4.5 kg Load bearing capacity: max. 40 kg WxHxD: 200 x 450.5 x 330 mm</p>	257049
PoE++ Extender		Art. No.
	<p>PoE++ Extender EC-940-HDI-O6H Cable type: ideally, CAT5e or better Supports Jumbo Frames up to a max. of 9 kB Input voltage: 52 ... 57 V DC Energy consumption: max. 80 W -20 ... +75 °C LxBxH: 126 x 95.3 x 30 mm</p>	256800

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.