

Linear luminaire With LED GRP industrial design



Technical Data

General:

Product Type: L402/4324-6120-152-1110-11-865S

Electrical Data:

Rated operational voltage AC: 220 ... 230 V

Rated operational voltage DC: 194 ... 250 V

Ambient Conditions:

Ambient temperature: -30 °C ... 45 °C Note: Through wiring Max. 3x16 A -30 °C ... 50 °C Note: Through wiring 2 Max. 3x10 A

Lighting Data:

Lamp wattage: 22 W

Lamp: LED

Light colour: 6500 K – daylight white

Light distribution: 120°x120°

Luminaire efficacy: 116 lm/W

Luminous flux: 2550 lm

Colour rendering: ≥ 80

Mechanical Data:

Translucent cover: Translucent

IP degree of protection (IEC 60598): IP66/IP67

Class: I (with inner PE connection)

Enclosure material: Polyester resin, Glass fibre reinforced

Enclosure colour: Light grey (RAL 7035)

Diffuser: Without diffuser

Sealing material: Silicone

Translucent cover material: Polycarbonate

Installed terminal strip: PE + N- + L+ + N' + L'

Max. solid connection terminals: 6 mm²

Type of connection cable: Finely stranded Solid

Size: 2

Impact strength (IEC 62262): IK10

Disconnection of the luminaire: No

Components:

Threaded plate: 2x plastic

Ballast: VG Luxtronic 40 W 300 mA

Through wiring: With 5 conductors 2.5 mm²

Drilled holes: 3 x M25

Example Type: L402/4324-6120-152-1110-11-865S | Art. No. 289700

Manufacturer: R. STAHL Schaltgeräte GmbH | Am Bahnhof 30 | 74638 WALDENBURG | r-stahl.com