

Linjelys med LED GRP industriutførelse



Technical Data

General:

Product Type: L402/4348-6100-152-2220-22-8500

Electrical Data:

Rated operational voltage AC: 100 ... 240 V

Rated operational voltage DC: 200 ... 250 V

Ambient Conditions:

Ambient temperature: -40 °C ... 55 °C Note: Through wiring maks. 3x16 A -40 °C ... 60 °C Note: Through wiring 2 maks. 3x10 A

Lighting Data:

Lamp wattage: 42 W

Lamp: LED

Light colour: 5000K - Nøytral hvit

Light distribution: 120°x120° med spredeglass

Luminaire efficacy: 138 lm/W

Luminous flux: 5810.00 lm

Colour rendering: ≥ 80

Mechanical Data:

Translucent cover: klar

IP degree of protection (IEC 60598): IP66/IP67

Class: I (med innvendig PE-tilkobl.)

Enclosure material: Polyester resin, glassfiberforsterket

Enclosure colour: lys grå (RAL 7035)

Diffuser: med diffusor

Sealing material: Silikon

Translucent cover material: Polykarbonat

Installed terminal strip: PE + N + L1 + L2 + L3

Max. solid connection terminals: 6 mm²

Type of connection cable: Finely stranded Solid

Size: 4

Impact strength (IEC 62262): IK10

Disconnection of the luminaire: Nei

Components:

Threaded plate: 2x rustfritt stål SS430

Ballast: VG Luxtronic 40W 300mA

Through wiring: med 5 ledere 2,5 mm²

Drilled holes: 3 x M20

Example Type: L402/4348-6100-152-2220-22-8500 | Art. No. 271365

Manufacturer: R. STAHL Schaltgeräte GmbH | Am Bahnhof 30 | 74638 WALDENBURG | r-stahl.com