


9002/11-137-029-001 Art. No. 158940



- For the intrinsically safe operation of a wide range of devices, such as HART transmitters, solenoid valves, sensors, zero-potential contacts and many more
- Compact, space-saving devices that are easy to install on a DIN rail
- Quick and efficient installation as barriers can be simultaneously snapped onto DIN rail and connected to ground (ISA - RPI12.06)

MY R. STAHL 9002A



The 9002 series INTRINSPAK two-channel zener barriers enable the intrinsically safe operation of virtually all field devices. The comprehensive portfolio and the combination of zener barriers cover a wide variety of signals. The devices are incredibly robust and require very little space. The back-up fuse is a convenient feature as it is standardized for all variants.

Technical Data

Explosion Protection	
Application range (zones)	2
Ex interface zone	0, 1, 2, 20, 21, 22
IECEEx gas certificate	IECEEx PTB 08.0057X
IECEEx gas explosion protection	Ex ec [ia Ga] IIC T4 Gc
IECEEx dust certificate	IECEEx PTB 08.0057X
IECEEx dust explosion protection	[Ex ia Da] IIIC
ATEX gas certificate	PTB 01 ATEX 2053 X
ATEX gas explosion protection	II 3 (1) G Ex ec [ia Ga] IIC T4 Gc
ATEX dust certificate	PTB 01 ATEX 2053 X
ATEX dust explosion protection	II (1) D [Ex ia Da] IIIC
FMus certificate	3010778
Marking FMus	NONINCENDIVE FOR, Class I, Div. 2, Groups A,B,C,D; T4; Class I, Zone 2, Group IIC T4 IS connections for Class I,II,III, Div. 1, Groups A,B,C,D,E,F,G; Class I, Zone 0, Groups IIC/IIB Hazardous location when inst. per doc. 90 026 11 31 1
Certificate ULus	E81680V1S3
Marking ULus	For use in Hazardous location, Class I, Div. 2, Groups A,B,C,D; T4 Providing IS circuits for Class I,II,III, GROUPS A,B,C,D,E,F,G; per doc. 90 026 11 31 3
cCSA certificate	1284580
Marking cCSA	Associated equipment [Ex ia], Class I, Div. 2, Groups A,B,C,D; Provides IS circuits for Class I,II,III, Class I, Zone 0, Groups IIC/IIB For applicable grps per inst. doc. 90 016 11 31 2
Inmetro gas certificate	UL-BR 12.0354
Inmetro dust certificate	UL-BR 12.0354

9002/11-137-029-001 Art. No. 158940

Explosion Protection	
Certificates	ATEX (PTB), Brazil (ULB), Canada (CSA), Canada (FM), China (CQST), IECEx (PTB), Japan (CML), Korea (KGS), USA (FM), USA (UL)
Declaration of Conformity	ATEX (EUK), China (CCC)
Installation	in Zone 2, Division 2 and in safe area
Further information	see respective certificate and operating instructions


Safety Data						
Max. voltage U_o/V_{oc}			13.7 V			
Max. current I_o/I_{sc}			14.5 mA			
Max. power P_o			50 mW			
Max. permissible external capacitance C_o/C_a for IIC			0.79 μ F			
Max. permissible external inductance L_o/L_a for IIC			160 mH			
Max. permissible external capacitance C_o/C_a for IIB			5 μ F			
Max. permissible external inductance L_o/L_a for IIB			560 mH			
Intrinsically safe limiting values Inductance L_o /capacitance C_o			Jointly connectable inductance L_o /capacitance C_o			
Channel 1	IIC	L_o [mH]	50 mH	1 mH	0.100 mH	
		C_o [μ F]	0.250 μ F	0.4800 μ F	0.7900 μ F	
	IIB	L_o [mH]	50 mH	1 mH	0.1 mH	
		C_o [μ F]	1.30 μ F	2.60 μ F	5 μ F	
Channel 2	IIC	L_o [mH]	50 mH	1 mH	0.1 mH	
		C_o [μ F]	0.250 μ F	0.480 μ F	0.790 μ F	
	IIB	L_o [mH]	50 mH	1 mH	0.1 mH	
		C_o [μ F]	1.30 μ F	2.60 μ F	5 μ F	
Channels 1 + 2	IIC	L_o [mH]	50 mH	1 mH	0.10 mH	
		C_o [μ F]	0.170 μ F	0.470 μ F	0.790 μ F	
	IIB	L_o [mH]	50 mH	1 mH	0.1 mH	
		C_o [μ F]	1.200 μ F	2.60 μ F	5 μ F	

Electrical Data							
Number of channels		2					
Maximum resistance R_{max}		978 Ω					
Min. resistance R_{min}		953 Ω					
Maximum output current I_{max}		10 mA					
Potential channel 1		Positive					
Potential channel 2		Positive					
Transmission frequency channel 1		$\leq$ 50 kHz					
Type of voltage		DC					
I_{leak} leakage current for U_n		$\leq$ 2 μ A					
Chan- nel	V_{nom}	I_{max}	R_{min}	R_{max}	U_o/V_{oc}	I_o/I_{sc}	P_o
1	10.00 V DC	10 mA	953 Ω	978 Ω	13.70 V	14.5 mA	50 mW
2	10 V	10 mA	953 Ω	978 Ω	13.70 V	14.5 mA	50 mW
1 + 2					13.70 V	29 mA	100 mW

9002/11-137-029-001 Art. No. 158940

Auxiliary Power	
Power supply	Controlled
Output	
Temperature influence	≤ 0,25 %/10K
Ambient Conditions	
Ambient temperature °C	-20 °C ... 60 °C
Ambient temperature °F	-4°F ... +140°F
Storage temperature °C	-20 °C ... 75 °C
Storage temperature °F	-4°F ... +167°F
Max. relative humidity	95% average, no condensation
Mechanical Data	
Degree of protection (IP)	IP40
Degree of protection (IP) terminals	IP20
Enclosure material	Polyamide 6GF
Number of connection terminals	4
Connection cross-section max.	1.5 mm²
Connection cross-section AWG	16 AWG
Type of connection cable	Solid Finely stranded
Width	103 mm
Width, inches	4.09 in
Length	12 mm
Length, inches	0.48 in
Depth of cut-out	72 mm
Mounting depth, inches	2.76 in
Weight	110 g
Weight	0.24 lb
Mounting / Installation	
Earthing connection cross-section	4 mm²
Earthing conductor cross-section AWG	12 AWG
Connection type	2 PA
Min. torque, Nm	0.5 Nm
Min. torque, lb/in	4.43 lb/in
Max. torque, Nm	0.6 Nm
Max. torque, lb/in	5.31 lb/in



Technical Drawings – Subject to Alterations




Dual-channel safety barriers, potential: + / +

9002/11-137-029-001 Art. No. 158940


Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Mounting on DIN rail NS 35/15






Mounting on DIN rail NS 32 by means of adaptor and mounting attachment, moulded plastic



Mounting on mounting plate by means of adaptor

Accessories

Terminal block		Art. No.
	Phoenix Contact terminal block UT 4-PE	113057
	Phoenix Contact terminal block UT 6-PE	113058
Adaptor		Art. No.
	Adaptor allows installation of a zener barrier Series 900x on a mounting plate of a previous series.	158826
Clamping base, moulded material		Art. No.
	Enables mounting of zener barrier on a G-rail.	165283
Fuse holder		Art. No.
	Fuse holder is snapped onto the side of the zener barrier and can be equipped with up to 5 back-up fuses (replacement).	158834

Spare Parts

Back-up fuse	Art. No.
--------------	----------

Zener Barriers
Dual-channel safety barrier



9002/11-137-029-001 Art. No. 158940

	For all zener barriers Series 9001, 9002 and 9004 unit: 5 pcs.	158964
Label carrier		Art. No.
	Transparent cover for the label	158977

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.