

- For redundant FO network structures (Profibus DP, Modbus RTU) in hazardous areas of Zone 1
- "Ex op is" interface makes for easy installation and maintenance
- With diagnostics function for early error detection and signaling

MY R. STAHL 9186B



The 9186 series FO fieldbus isolating repeater transmits PROFIBUS DP and Modbus RTU signals over distances of up to 1.2 mi / 2 km as part of redundant fiber optic network structures. Standard plug connectors can be connected to the inherently safe optical interfaces "Ex op is". The diagnostic functions detect critical signal conditions early and report them to the control room.

Technical Data

Explosion Protection	
Application range (zones)	2
Ex interface zone	2, 22
IECEX gas certificate	IECEX BVS 13.0107 X
IECEX gas explosion protection	Ex nA nC [op is T6 Ga] IIC T4 Gc
IECEX dust certificate	IECEX BVS 13.0107 X
IECEX dust explosion protection	[Ex op is Da] IIIC
ATEX gas certificate	BVS 07 ATEX 068 X
ATEX gas explosion protection	⊕ II 3 (1) G Ex nA nC [op is T6 Ga] IIC T4 Gc
ATEX dust certificate	BVS 07 ATEX 068 X
ATEX dust explosion protection	⊕ II (1) D [Ex op is Da] IIIC
cULus certificate	E81680
Marking cULus	Class I, Zone 2, AEx/Ex nC Group IIC
Certificates	ATEX (BVS), Brazil (ULB), Canada (UL), IECEX (BVS), USA (UL)
Ship approval	CCS, EU RO MR (DNV)
Installation	Cl. I, Div. 2; Cl. I, Zone 2; Zone 2 or safe area
Electrical Data	
LFD relay	Yes
Protocols	PROFIBUS DP
Data rate	9.6 kbit/s ... 1.5 Mbit/s
Electric interface version	RS 485
Electric interface connection	Sub-D socket X1, 9-pole
Field side of interfaces	Ex opis Fibre optics
Protocols optical interface	Protocol-transparent with RS-485 interface
Network structure	Point-to-point End of line
Optical interface connection	ST®, BFOC/2.5 socket

Electrical Data

Optical interface transmission distance	≤ 2000 m
Data transmission display	green TD and RD
Error control	Power supply failure: Fault-contact is open Transmission level is good: LED green and yellow "FO signal", fault-contact is closed. Transmission level reduced (-1,5 dBm): LED yellow "FO ERR", fault-contact is open. Fiber breakage or transmission level is too low (-3 dBm): LED red "FO ERR", fault-contact is open.
FO wavelength	850 nm
Compatibility	Compatible with series 9186

<p>Connection diagram 9186/25</p>		<table border="1"> <thead> <tr> <th>PIN</th> <th>RS 485</th> </tr> </thead> <tbody> <tr> <td>8</td> <td>A-</td> </tr> <tr> <td>3</td> <td>B+</td> </tr> <tr> <td>6</td> <td>U+</td> </tr> <tr> <td>5</td> <td>GND</td> </tr> </tbody> </table>	PIN	RS 485	8	A-	3	B+	6	U+	5	GND
PIN	RS 485											
8	A-											
3	B+											
6	U+											
5	GND											

Auxiliary Power

Auxiliary power	24 V DC
Nominal voltage V_{nom}	24 V DC
Auxiliary power voltage range	18 ... 31.2 V
Voltage range residual ripple	≤ 3,6 V_{SS}
Nominal current	130 mA
Power consumption	3 W
Polarity reversal protection	Yes
Operation indication	Green "PWR" LED

Galvanic Isolation

Auxiliary power to RS-485	1.5 kV AC
---------------------------	-----------

Output

Fault message contact switching capacity	max. 60 V DC; 42 V AC; 0,46 A
Display error	Red "ERR" LED

Ambient Conditions

Ambient temperature °C	-20 °C ... +60 °C
Ambient temperature °F	-4°F ... +140°F
Storage temperature °C	-40°C ... +85°C
Storage temperature °F	-40°F ... +185°F
Max. relative humidity	95%
Use at the height of	< 2000 m
Note	Class II,III, Div. 2 and NEC® 506 Zone 22 applications are possible; contact factory

Mechanical Data

Degree of protection (IP)	IP30
Degree of protection (IP) terminals	IP20
Fire resistance (UL 94)	V0


Mechanical Data

Enclosure material	Polyamide
Min. rigid conductor cross section	0.2 mm ²
Max. rigid conductor cross section	2.5 mm ²
Min. flexible conductor cross section	0.2 mm ²
Max. flexible conductor cross section	2.5 mm ²
Connection cross-section	0.2 to 2.5 mm ² flexible 0.2 to 2.5 mm ² rigid 0.25 to 2.5 mm ² flexible with core end sleeve
Connection cross-section AWG	24 ... 14
Width	35.2 mm
Width, inches	1.38 in
Height	114.2 mm
Height in inches	4.49 in
Length	106 mm
Length in inches	4.17 in
Weight	244 g

Mounting / Installation

Grid dimension	35.2 mm
Mounting orientation	Vertical Horizontal
Connection type	Screw terminal

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Type 9186/25

Accessories

Sub-D plug, RS-485



9-pin for connecting fieldbus or ServiceBus to CPU & power module Type 9440/15, 9185 field-busisolatingrepeater and 9786/15-12 media converter.
The end-of-line resistor is installed and switchable. For non-intrinsically safe RS-485.
Ambient temperature: -40 °C to +75 °C

Art. No.

105715

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.