

Camera and Video systems

Pan-tilt-zoom IP camera and illuminator



EC-951-V6C02L8R2T1MV00 Art. No. 294439



- PTZ camera with additional IR illuminator for object detection at night
- With "dynamic masking" for anonymisation and video analytics function for detection object
- Full HD, low-light technology, ONVIF Q, S, T, electronic image stabilisation, and direct fibre optic connection
- Extremely fast rotating, extremely precise and up to 218 presets
- Ambient temperature -40° ... +65 °C
- Certified for hazardous areas Zone 1, 2, 21, 22, according to ATEX, ATEX, IECEx, NEC / CEC, Lloyd's

MY R. STAHL EC951A



ONVIF 000



The EC-951 PTZ camera version is an extended version of the EC-941 camera and comes with an additional IR illuminator. The camera provides excellent object detection in dark or low-light situations at a range of up to 200 m.

All cameras come with the „dynamic masking“ feature to anonymise video data of faces so that are no longer identifiable according to relevant privacy regulations. This variant is also equipped with a video analysis function for object recognition and object tracking of strangers and objects in companies.

Technical Data

Explosion Protection

Application range (zones)	1, 2, 21, 22
IECEX gas certificate	ULD 16.0005X
IECEX gas explosion protection	Ex db IIC T6...T4 Gb
IECEX dust certificate	ULD 16.0005X
IECEX dust explosion protection	Ex tb IIIC T85°C...T135°C Db
ATEX gas certificate	16 ATEX 1674X
ATEX gas explosion protection	Ex II 2 G Ex db IIC T6...T4 Gb
ATEX dust certificate	16 ATEX 1674X
ATEX dust explosion protection	Ex II 2 D Ex tb IIIC T85°C...T135
cULus certificate	E482740
Lloyd's Register categories	ENV1, ENV2, ENV3, ENV5

Electrical Data

Rated operational voltage AC	100 V
Rated operational voltage DC	
Rated operational current AC	1.2 A
Power consumption	120 W
Interfaces	SFP port & RJ45 socket
Connection	10/100Base-T, 100Base FX
I/O alarm	1x alarm input
I/O relay	2x relay output

Camera Data

Sensor	1/2.8" Exmor R CMOS
Lens	f = 4.3 (w) to 129 mm (t) From F1.6 to F14
Viewing angle	63.7° to 2.3° H, 38.5° to 1.3° V

Camera and Video systems

Pan-tilt-zoom IP camera and illuminator



EC-951-V6C02L8R2T1MV00 Art. No. 294439

Camera Data

Focus	Auto, manual, trigger
Zoom	30x (360x digital zoom)
Resolution	Full HD 1080p 1920x1080 pixels
Pixel	2.13 megapixels
Number of preset positions	Up to 250
Accuracy of preset positions	0.02 °
Horizontal speed (variable)	0,1°/s ... 100°/s
Vertical speed (variable)	0,1°/s ... 100°/s
Frame rate (fps)	1 to 60 frames per second
Back light compensation	On/Off
Compression	H.264, MJPEG, JPEG, MPEG4
No. of privacy maskings	24 (8 simultaneously)
De-fog	Off/Low/Mid/High
WDR (dynamic range)	120 dB
White balance	AWB, ATW, internal, external (Fixed, auto), sodium vapour lamp (Fixed, auto, external auto)
Wide Dynamik Range	On/Off Light level, selection of Brightness compensation Light compensation level
Motion detection	Yes
Web server	Yes

Software

Network protocol	ONVIF profile S and T
Network Configuration	TCP/IPv4-IPv6, UDP/IPv4-IP6, HTTP, HTTPS, NTP, DHCP, WS-DISCOVERY, DSCP, IGMP (Multicast), SOAP, DNS, SNMP
Streaming	RTSP, RTCP, RTP/IPv4, HTTP Multicast
Video analysis technology	Video Analytics & Autotracking

Ambient Conditions

Cold start range (with heating)	-40°C up to -10°C
---------------------------------	-------------------

Mechanical Data

Version	Video analytics & autotracking Low light camera + illuminator
Degree of protection (IP)	IP66, 67, 68, 69
Enclosure material	Stainless steel 316L
Cable length	0 m
Opening for cable gland	2 x 3/4" NPT
Slewing range	360° continuous
Tilt range	-90° ... +90°
Integrated wiper	Yes
Package weight	35 kg
Package dimensions	540 x 310 x 490 mm
Weight	31 kg
Weight	68.34 lb


Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations

Accessories

EC-951-V6C02L8R2T1MV00 Art. No. 294439

Camera multi-cable armored

Art. No.



VB-CAM-MULTI-Ethernet-ARM
 1 x Ethernet cable
 3 x power supplies 2.5 mm² / AWG14
 7 x data cable 0.34 mm² / AWG22
 -60 °C ... +80 °C [-76 °F ... +176 °F]
 19.2 ±0.5 mm [0.76 ±0.02 inches] outer diameter
 IEC 60332-1 flame-resistant
 IEC 60754-2 halogen-free
 DIN 60811-404 oil-resistant
 NEK 606 mud-resistant

252571

Ex e Terminal box

Art. No.



JCT-8146-Ethernet+Analog 5xcable glands
 Terminal box, polyester resin
 Version for ethernet Tx or analog cameras
 Dimensions without cable glands (HxWxD): 340.5 mm x 340.5 mm x 91 mm
 Ingress protection: IP66
 equipped with:
 5 x cable glands:
 2 x CMP-25SC2KVAR KLE MsNi M25x1.5
 1 x 8161/7-M25-1707 with red stopping plug
 2 x 8161/7-M20-1304 with red stopping plug
 usable for:
 EC-750, EC-910-AFZ, EC-940S-AFZ (ATEX, IECEx)
 EC-840S-TIC (ATEX, IECEx), EC-94x-PTZ, Water tank

265668

JCT-8146-22P-FO-BOX-4xM20-1xM25-R1.1
 Terminal box, polyester resin
 Version for ethernet Tx and Fx, IP cameras
 Dimensions (HxWxD): 340.5 mm x 340.5 mm x 91 mm
 screwed lid
 Protection class: IP 66
 Including TAG label (Formica)
 equipped with:
 01x Telegärtner mounting rail distributor (6x SC Duplex)
 20x Phoenix terminal block UT 2.5
 02x Phoenix protective conductor terminal USLKG5
 Cable entries:
 01x brass plate
 01x CMP 20sA2F M20, MsNi
 01x CMP 20s16A2F M20, MsNi
 02x M20 sealing plugs, nickel-plated brass (enclosed)
 02x CMP 20sC2K M20, MsNi
 01x CMP 25SC2KVAR M25, MsNi
 usable for:
 EC-941-PTZ

286343

Wall bracket

Art. No.



WB-EC-940-PTZ/EC-941
 Wall bracket for EC-940-PTZ and EC-941
 Material: 316L (1.4404) stainless steel, electropolished
 Load capacity: max. 40 kg [88.18 lb]
 Length: 400 mm [15.75 inches]

251364

Camera and Video systems

Pan-tilt-zoom IP camera and illuminator



EC-951-V6C02L8R2T1MV00 Art. No. 294439

Pole mounting

Art. No.



PMA-EC-940-PTZ/EC-941

Pole mount adaptor for EC-940-PTZ and EC-941
 Material: 316L (1.4404) stainless steel, electropolished
 For pole diameter 110 ... 150 mm [4.33 ... 5.9 inches]
 Load capacity: max. 50 kg [110.23 lb]
 Only together with wall bracket WB-EC-940-PTZ/EC-941

251362

Corner adapter module

Art. No.



CMA-EC-940-PTZ/EC-941

Corner adapter module EC-940-PTZ and EC-941
 Material: 316L (1.4404) stainless steel, electropolished
 Capacity: max. 50 kg [110.23 lb]
 WxH: 335 x 186 mm [13.19 x 7.32 inches]
 Only together with wall bracket WB-EC-940-PTZ/EC-941

251363

Parapet mounting bracket

Art. No.



PB-EC-940-PTZ/EC-941

Parapet mounting bracket for EC-940-PTZ and EC-941
 Material: 316L (1.4404) stainless steel, electropolished
 Load capacity: max. 40 kg [88.18 lb]
 Diameter: 238 mm [9.37 inches]

251365

Power line filter

Art. No.



EMC filter TDK, 1phase, 250VAC, 6A

EPCOS / TDK B84112G0000B060
 Mandatory for use of cameras in maritime applications
 Filter Type: EMC Power Line Filter
 Voltage Rating: 250 V
 Current Rating: 6 A
 Mounting Style: Chassis Mount
 Termination Style: Tab Connector
 Leakage Current: 0.369 mA
 Operating Frequency: 50 Hz / 60 Hz
 Construction
 2-line filter
 Metal case
 Polyurethane potting (UL 94 V-0)
 ENEC, UL and cUL approval

279754

Water tank

Art. No.



WaterTank 10-PV-A

316L (1.4404) stainless-steel enclosure, electropolished
 Capacity 10 litres
 Pressure generation by manual pumping or with compressed air
 Pressure: max 4 bar
 24 V AC/DC, max 20 W
 Temp. range -40 °C to +60 °C / [-40 °F to +140 °F] (depending on freezing point of liquid used)
 ATEX certified Zone 1, 2
 Suitable for EC-94x-PTZ and EC-940S-AFZ

251366

Camera and Video systems



Pan-tilt-zoom IP camera and illuminator



EC-951-V6C02L8R2T1MV00 Art. No. 294439


Cable glands

Art. No.

	<p>CMP-20s16PXSS2K-REX KLE MsNi 3/4" OR Metal cable gland explosion protected for unarmoured cable Clamping range: 3.1 ... 8.6 mm Potting compound 250599 CMP-RAPIDEX30 is additionally required</p>	<p>282717</p>
	<p>CMP-20sPXSS2K-REX KLE MsNi 3/4" OR Metal cable gland explosion protected for unarmoured cable Clamping range: 6.1 ... 11.7 mm Potting compound 250599 CMP-RAPIDEX30 is additionally required</p>	<p>282687</p>
	<p>CMP-25sPX2K-REX cab.gl. n-pl. br. NPT 3/4" Metal cable gland Explosion-protected For armoured cables (suitable for 252571 VB-CAM-MULTI-Ethernet-ARM cables) Cable dia. range: 14 to 22 mm 250599 CMP-RAPIDEX30 compound is also required</p>	<p>251734</p>

SFP Module

Art. No.

	<p>SFP Moxa SFP-1FEMLC-T Can be used in camera EC-941 Transmission: multi-mode Power consumption: max. 1 W Bandwidth: 100Base-FX / 100MBit/s Wavelength: 1310 nm Connector: LC duplex Distance: 2 km / 4 km Temperature range: -40 ° C ... + 85 ° C</p>	<p>282714</p>
	<p>SFP Barox AC-SFP-FXMME 100MB MM T Can be used in Barox Switch in safe areas, not useable in camera EC-941 Transmission: multi-mode Bandwidth: 100Base-FX / 100MBit/s Wavelength: 1310 nm Connector: LC duplex Distance: 2 km Temperature range: -40 ° C ... + 85 ° C</p>	<p>276421</p>

Spare Parts

Potting compound

Art. No.

	<p>CMP-RAPIDEX30 Potting compound for cable glands</p>	<p>250599</p>
--	--	---------------

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.