

# Lighting

## Linear luminaire With LED

GRP

6402/4128-9100-150-2220-22-8750 Art. No. 311193



- State-of-the-art LED technology with high luminous efficacy and long service life
- Extremely high luminaire efficacy
- Luminous flux after 100,000 h still 90% of the starting luminous flux
- Optionally with DALI for controlling and monitoring the luminaire
- Optionally with address modules for directly actuation of a common battery system

MY R. STAHL 6402C



The linear luminaire with Series 6402/4 LED is ideal for lighting surfaces at a mounting height of up to 10 m. It can also be used to illuminate equipment and objects, both inside and outside. The pole mounting sleeve accessory can be used to easily mount the luminaire on poles. Optionally, the luminaire can be equipped with an address module. It can be used to control and monitor the luminaire for the common battery systems.

### Technical Data

#### Explosion Protection

|                                 |   |
|---------------------------------|---|
| Ex version                      | Yes   |
| Application range (zones)       | 2, 21, 22                                   |
| IECEX gas certificate           | IECEX IBE 14.0080                           |
| IECEX gas certificate           | IECEX IBE 14.0080                           |
| IECEX gas explosion protection  | Ex ec IIC T4 Gc                             |
| IECEX dust certificate          | IECEX IBE 14.0080                           |
| IECEX dust explosion protection | Ex tb op is / tc IIIC T100 °C Db            |
| ATEX gas certificate            | IBExU 14 ATEX 1292                          |
| ATEX gas certificate            | IBExU 14 ATEX 1292                          |
| ATEX gas explosion protection   | ⊕ II 3 G Ex ec IIC T4 Gc                    |
| ATEX dust certificate           | IBExU 14 ATEX 1292                          |
| ATEX dust explosion protection  | ⊕ II 2 D Ex tb op is / tc IIIC T100 °C Db   |
| Certificates and approvals      | ATEX<br>IECEX<br>UKEX                       |
| Certificates                    | ATEX (IBE), IECEX (IBE)                     |
| Declaration of conformity       | ATEX (EUK), Declaration of Conformity (AUS) |

#### Electrical Data

|                              |               |
|------------------------------|---------------|
| Rated operational voltage AC | 220 ... 240 V |
| Rated operational voltage DC | 196 ... 250 V |
| Frequency range              | 50 – 60Hz     |

#### Lighting Data

|                 |                     |
|-----------------|---------------------|
| Number of lamps | 1                   |
| Lamp wattage    | 22 W                |
| Lamp            | LED                 |
| Light colour    | 5700 K – cool white |

# Lighting

## Linear luminaire With LED

### GRP

6402/4128-9100-150-2220-22-8750 Art. No. 311193



#### Lighting Data

|                    |                                |
|--------------------|--------------------------------|
| Light distribution | 120°x120° with diffusing glass |
| Luminaire efficacy | 132 lm/W                       |
| Luminous flux      | 2910 lm                        |
| Colour rendering   | ≥ 80                           |
| Colour temperature | 5700 K                         |

#### Ambient Conditions

|                        |  |
|------------------------|--|
| Ambient temperature °C | -40 °C ... 50 °C (T100 °C) Note: Through wiring Max. 3x16 A<br>-40 °C ... 55 °C (T100 °C) Note: Through wiring 2 Max. 3x10 A |
|------------------------|--|

#### Mechanical Data

|   |   |
|---|---|
| Version                                   | Standard                                |
| IP degree of protection (IEC 60598)       | IP66/IP67                               |
| Enclosure material                        | Polyester resin, Glass fibre reinforced |
| Enclosure color                           | Light grey (RAL 7035)                   |
| Diffuser                                  | With diffuser                           |
| Sealing material                          | Silicone                                |
| Silicone-free content                     | Contains silicone                       |
| Translucent cover material                | Polycarbonate                           |
| Installed terminal strip                  | PE + N + L1 + L2 + L3                   |
| Max. solid connection terminals           | 6 mm <sup>2</sup>                       |
| Max. finely stranded connection terminals | 4 mm <sup>2</sup>                       |
| Type of connection cable                  | Finely stranded<br>Solid                |
| Size                                      | 2                                       |
| Width                                     | 184 mm                                  |
| Height                                    | 125 mm                                  |
| Length                                    | 700 mm                                  |
| Impact strength (IEC 62262)               | IK10                                    |
| Weight                                    | 3.3 kg                                  |
| Weight                                    | 7.28 lb                                 |
| Disconnection of the luminaire            | No                                      |

#### Components

|                          |                                |
|--------------------------|--------------------------------|
| Threaded plate           | 2x SS430 stainless steel       |
| Ballast                  | CG Luxtronic 48 W 300mA (91)   |
| Through wiring           | without                        |
| Drilled holes            | 3 x M20                        |
| Cable glands and entries | can be ordered as an accessory |
| Stopping plugs           | Can be ordered as accessories  |
| Accessories              | without                        |

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations

## Accessories

Breather

Art. No.




# Lighting


## Linear luminaire With LED


GRP


6402/4128-9100-150-2220-22-8750 Art. No. 311193





|  |   |        |
|--|---|--------|
|  | Thread: M25 x 1.5 (20 pieces); without jam nut  | 285780 |
|  | Thread: M25 x 1.5 (1 piece); for installation in light fittings; made from stainless steel; without jam nut | 296608 |
|  | M25 x 1.5 in order to avoid condensate formation  | 115738 |


| Ceiling and wall mounting bracket  |  | Art. No. |
|--|--|----------|
|  | mounted on a mounting rail for a variable mounting distance; Material: stainless steel; Lamp can be swiveled in steps of 15°; 1 pair | 222827   |

| Holder for translucent cover   |   | Art. No. |
|--|---|----------|
|  | The fall prevention system for the light fitting cover prevents the light fitting cover from falling accidentally when the light fitting is opened. | 226791   |

| Mounting bracket   |  | Art. No. |
|--|--|----------|
|  | mounting clamp mounted on a mounting rail for a variable mounting distance; 1 pair | 222456   |

| Mounting rail  |  | Art. No. |
|--|--|----------|
|  | for a variable mounting distance; 1 pair | 222826   |

| Pipe clamp   |  | Art. No. |
|--|--|----------|
|  | R 1 1/2"; with mounting rail for a variable mounting distance; material: stainless steel; 1 pair | 222459   |
|  | R 1 1/4"; with mounting rail for a variable mounting distance; Material: stainless steel; 1 pair | 222458   |
|  | R 2"; with mounting rail for a variable mounting distance; Material: stainless steel; 1 pair     | 222460   |

| Pole mounting sleeve   |   | Art. No. |
|--|---|----------|
|  | for the subsequent mounting on lights size 2 and size 4, completely with assembly parts (for pipe diameter 42 mm) | 227512   |

# Lighting

Linear luminaire With LED


GRP

6402/4128-9100-150-2220-22-8750 Art. No. 311193



## Protection against accidental contact

Art. No.



The protection against accidental contact prevents maintenance technicians and electrical installers from accidentally touching conductive parts. The degree of protection is increased to IP20 when the protection against accidental contact is used.

283153

## Ring bolt

Art. No.




M8, direct mounting in insert nuts; 1 pair

115736

## Socket wrench

Art. No.



M8 / A/F 13;  
For actuating the central lock

222430

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.