

IS-TH1MR.1 Trigger Set mid BR Art. No. 319887



- Reliable data capture and processing of 1D or 2D barcodes
- direct data transfer via ISM interface
- power supply via connected device, thus no battery required
- direct interface connection with device, no Bluetooth® required

**MY R. STAHL MPERIPHER-ALSA**

The mobile multifunctional set consisting of a Trigger Handle (hand-held barcode scanner) and the IS530.x industrial smartphone is a flexible duo for reliable data capture in hazardous areas. The HID-active, ready-to-use high-performance scanner captures any 1D or 2D barcodes at close range of up to 6 metres or distances up to 18 metres via the reliable Zebra OEM imager scan engines. The data is further processed directly via the IS530.x smartphone connected via the ISM interface.

**Technical Data**

<b>General</b>	
Technology	Barcode scanner
<b>Explosion Protection</b>	
Ex version	Yes
Application range (zones)	1 & 2, 21 & 22
Application range (zones)	1, 2, 21, 22
Application range	Zone 1, Zone 21 Zone 2, Zone 22
Scope	Brazil (INMETRO)
INMETRO certification	BRA 22.GE0005X
INMETRO gas explosion protection	Ex ib op is IIC T4 Gb
INMETRO dust explosion protection	Ex ib op is IIIC T135°C Db
<b>Auxiliary Power</b>	
Power supply	via smartphone
<b>Ambient Conditions</b>	
Ambient temperature	-20 – 60
<b>Mechanical Data</b>	
Version	mid-range 8m
Front enclosure protection type (IP)	IP68
Rear enclosure protection type (IP)	IP68
Enclosure material	Plastic
Width	90 mm
Height	202 mm
Depth	125 mm
Weight	1 kg
Weight	2.2 lb

IS-TH1MR.1 Trigger Set mid BR Art. No. 319887

---

**Mounting / Installation**

Connection type	Smartphone IS530.1
-----------------	--------------------

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.